

Shop Order

Carroll County Ambulance Service Daniel Myers 829 Polk St Carrollton, KY 41008 502.732.7038 james.myersii@cchmc.org

R.S.V.P., Inc. Mack Arnos 5265 Tractor Rd. Suite "F" PO BOX 6888 Toledo, OH 43612 419.764.4499 mack@rsvpambulance.com

04/08/2023 Exp. Date: Quote No: 10036-0046

08/18/2023 Job/Order No: 22OF 28438XA Page 1

| 00/10/2023 | 30b/Oldel No. 2201 20430XA | | i age i |
|------------|---|-----|---------|
| PART NO | S DESCRIPTION | QTY | ID |
| | == ***********BID STANDARDS********* - 36.001 03/06/23 == | | AEV |
| 00-00-0010 | ORDER NUMBER | 1 | AEV |
| 00-00-0107 | Order Date: Post August 1st, 2022 | 1 | AEV |
| 00-00-0212 | < Ambulance Built to CAAS GVS 3.0 Certification | 1 | AEV |
| | CAAS GVS 2.0 Certification issued, Sticker issued for completed Vehicle. | | |
| | Exception report generated as necessary. | | |
| | Payload Capacity > minimum per vehicle with optional permanently mounte | :d | |
| | equipment shall be per the ambulance type. | | |
| | Weight spreadsheet shall calculate each seating position at 175 lbs. | | |
| | Weight analysis per CAAS GVS table. | | |
| | Additional Exceptions to print or report out when chosen. | | |
| | >>> | | |
| | >> Backup camera is required on every model, please ensure to add << | | |
| | | | |
| 00-00-0220 | < > Upgrade suggestions to sales to meet CAAS GVS 3.0 | | AEV |
| | The following items shall be reviewed with the customer, and added or take a | an | |
| | exception to CAAS GVS 2.0 | | |
| | >> Backup alarm Must NOT have a disable switch. << | | |
| | >Front OEM bumper must remain OEM, all others are an exception | | |
| | >> | | |
| | >C.18.7 FSAM (AEV) does not provide a final BOM per vehicle, no option to meet. | | |
| | > C.9.6 rear bumper must contain open bar grate design. (AEV std flip step meet | ts, | |
| | provided not modified. | | |
| | >C.10.2 pass thru cab connection must be latching, | | |
| | >on-board permanent mount suction system required | | |
| | >trash enclosure to have a latching lid. | | |
| | > 2nd Fire Extinguisher to be added to the order, installed. | | |
| | | | |
| 00-00-0406 | Vehicle Destination any state other than Connecticut | | AEV |
| 00-10-0015 | Vehicle Quantity (Vehicles) | | AEV |
| 00-91-0003 | CHASSIS VIN NUMBER: | 1 | AEV |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 2 |
|------------|---|------|--------|
| PART NO | S DESCRIPTION | QTY | ID |
| 00-91-0021 | ACCOUNT SPECIALIST: Randall Pennington | 1 | AEV |
| 00-91-0027 | REFERENCE UNIT #: | 1 | AEV |
| 00-91-0028 | RE-WRITE DATE : | 1 | AEV |
| 00-91-0040 | SEAT BELT POSITIONS MODS | 1 | AEV |
| 00-91-0042 | CAB SEAT BELT MOD: | ' 1 | AEV |
| | | | |
| 00-91-0044 | Total: 2 Seated Positions in Chassis Cab | 1 | AEV |
| 00-91-0050 | REAR SEAT BELT MOD: | 1 | AEV |
| 00-91-0054 | Total: 4 Seated Positions & One Floor Mount Secured Patient | 1 | AEV |
| 00-99-9000 | Revision Level: 0 - Zero - ORIGINAL VERSION | 1 | AEV |
| 00-99-9030 | Change Order Level: 0 - Zero - ORIGINAL VERSION | 1 | AEV |
| 00 00 0000 | > Aluminum - Expanded PVC Cabinet Configuration | | AEV |
| | == ******F-Series 108ca CHASSIS******** - 36.001 03/06/23 == | | AEV |
| 04.45.0000 | | | |
| 01-1F-0000 | Type I AEV Traumahawk Modular Ambulance | | AEV |
| 01-AT-1F48 | S < > 2022 Ford, F-550 4 x 4 DRW Reg Cab, 193" WB, XLT Turbo Diesel | 1 | AEV |
| | 22OF28438XW | | |
| | VIN 1FDUF5HT1NDA17879 | | |
| | | | |
| 01-FM-4WH3 | > Wheel Finish: Polished SS Wheel Simulators (F-550) | 1 | AEV |
| | | | |
| 01-FM-DL01 | > Cab Door Locks: Power XLT- Auto Lock,Auto Unlock Standard | 1 | AEV |
| 01-SZ-0008 | < > Ford Type 1 F OEM Backup camera Kit ,Declined, Use different | 1 | AEV |
| | camera ILOS | | |
| | Return camera kit and harness system to PDI group, Keep at AEV. | | |
| | | | |
| 01-TP-0021 | > Tire Pressure Monitoring System: Doran 360HD6. (6) Tires | 1 | AEV |
| | 1 | 1 | |
| 04-SU-1101 | Ford OEM Front Suspension Coil Spring Std F-450/550 | 1 | AEV |
| | < > Liquid Spring Rear Suspension: F-550 , 2017+ | | AEV |
| | *NOTE: If Oxygen Lift is installed, then if the O2 Cmpt Door is open, the knee | ling | |
| | suspension will not dump until door is closed* | | |
| | | | |
| | | | |
| 01-TT-0208 | < I ""DETAIL"" Liquid Rear Suspension Decal Install | 1 | AEV |
| 01-11-0206 | ==:/= =:-quita : tean europerioien = eean metam | | AEV |
| | Prior to delivery, detail department is to install a Black Decal on the dash: | | |
| | | | |
| 04-SU-0601 | Kneeling Feature: Enable Switch Located in CAB console | 1 | AEV |
| 04-SU-0610 | Kneeling Feature: Activated by TRAILING rear access door | 1 | AEV |
| 04-SU-0614 | > Kneeling Feature: Activated by MOMENTARY switch. IATS | 1 | AEV |
| | | ' | |
| 04-SU-0612 | S LOCATION: Sw panel at face of SB near Side access doorr | 7 | AEV |
| 04-SU-0651 | Exhaust system termination point: OEM Location, Rt Rear | 1 | AEV |
| 04-SU-2024 | Liquid spring controller installed on driver side of console, | 1 | AEV |
| | recessed forward | | |
| | see console print | | |
| | 555 55115515 p.m.t | | |
| 04 CH 220C | Dearlimid Coring Company Lon 0 2022 Ford 8 Days | 1 | AEV |
| 04-SU-220S | Rear Liquid Spring Surcharge Jan 9 2023 Ford & Ram | 1 | |
| 04-SU-03F6 | Rear Stabilize (Anti-Sway) Bar: OEM, Ford F-450/550 | 1 | AEV |
| | == 172 x 96 T-1 LWB Ford X-Series, Conversion - 36.001 03/06/23 == | | AEV |
| 06-EA-01FD | Tire Valve Extensions, S/S Braided, PR, Dual Rear Wheel | 1 | AEV |
| 01-Y0-0002 | > BODY Generation 10 | 1 | AEV |
| 01-X0-0002 | < Body Certification Provided to Specification -Gen 10 | 1 | AEV |
| 01-70-0002 | | • | ALV |
| | The Body Manufacturing group certifies that this Ambulance Modular body has be | | |
| | constructed of materials and methods that meet or exceed the standards as require | | |
| | by the AEV Generation 10 Body Specification of February 24, 2022 as published | ed. | |
| | The body shall be built and constructed to the submitted work order and the A | EV | |
| | Generation 10 build standards without exception. Any Deviations to the work or | | |
| | or Generation 10 build standards must have written authorization prior to bo | | |
| | | чy | |
| | delivery to AEV by the AEV Body Engineer on file. | | |
| | | | |
| 02-00-0002 | < > Body Build Information | 1 | AEV |
| | Body Number; | | |
| | Account Manager; | | |
| | | | |
| | Chassis Type: | | |
| | Mickey Body Due Date; | | |
| | | | |

| 08/18/2023 | Job/Order No: 22UF 28438XA | OTV | Page 3 |
|--------------------------|---|----------|------------|
| PART NO 02-00-0003 | S DESCRIPTION < I ALL DIMENSIONS ON ORDER WILL HAVE A VARIABLE OF + OR - 1/4" | QTY | ID AEV |
| 02-00-0003 | ALL DIMENSIONS ON ORDER WILL HAVE A VARIABLE OF + OR - 1/4" Unless specified as a minimum dimension. | 1 | AEV |
| | Offiess specified as a minimum diffiension. | | |
| 02-B0-CF01 | Compartment Surface Finish: D.A. Sanded Aluminum | 1 | AEV |
| 02-B0-CF01 | > Compartment Surface Finish: Speed Liner, Gray - M-1 | 1 | AEV |
| 02-B0-CFN1 | < > Component Finish (Shelf/Tray/Divider): Speedliner Each | 1 | AEV |
| 02-20-01111 | Choice of BLACK or GRAY coating | | 7.2 4 |
| | Onclose of BERtort of Civit occurry | | |
| 02-B0-CFO2 | > Compartment Surface Finish: Speed Liner, Gray - M-2 | 1 | AEV |
| 02-B0-CFN1 | < > Component Finish (Shelf/Tray/Divider): Speedliner Each | 1 | AEV |
| | Choice of BLACK or GRAY coating | | |
| | · | | |
| 02-B0-CFO3 | > Compartment Surface Finish: Speed Liner, Gray - M-3 | 1 | |
| 02-B0-CFN1 | < > Component Finish (Shelf/Tray/Divider): Speedliner Each | 1 | AEV |
| | Choice of BLACK or GRAY coating | | |
| | | | |
| 02-B0-CFO5 | > Compartment Surface Finish: Speed Liner, Gray - M-5 | 1 | AEV |
| 02-B0-CFN1 | < > Component Finish (Shelf/Tray/Divider): Speedliner Each | 1 | AEV |
| | Choice of BLACK or GRAY coating | | |
| 02 P2 VO02 | Rody Mod: Type 1 I MR 179" v 06" v 79" Interior LD 6" Dady Dron v | 1 | AEV |
| 02-B2-XO92 02-00-0006 | Body, Mod: Type 1 LWB, 172" x 96" x 72" Interior HR - 6" Body Drop x Headroom: 72" Finished Interior - Ducted A/C | 1 | AEV AEV |
| 02-00-0000 | Readroom: 72 Finished Interior - Ducted A/C Compartment and Entry door Full length Stainless Steel Hinges std | | AEV |
| 02-B0-CC01 | Compartment and Entry door Full length Stallness Steel Finges std | 1 | AEV |
| 02-00-0001 | Sides and Back: .100 Polished Aluminum Diamond Plate | 1 | ALV |
| | Compartment Ceiling: .090 Aluminum Sheet | | |
| | Compartment Coming. 1000 Aluminam Chect | | |
| 02-B0-SFL0 | Compt Floors: Sweep-out, even with bottom door jamb | 1 | AEV |
| | Unless Specified Otherwise. | | |
| | · | | |
| 02-B0-CC41 | > Compartment floor thickness .125" standard | 1 | AEV |
| 02-B0-CC18 | Compartment Ventilation - Flap style #VT-2495-A01, STD | 1 | AEV |
| 02-B0-CEX2 | Curbside Entry Door (CSE): 84.813"H x 31.0"W X w/6" drop T1 T9 | 1 | AEV |
| 02-B0-09B2 | C/S Door Check : Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 02-B0-CESL | Curbside Entry Door (CSE) Location: Standard, Rearward of M-7 Compt | 1 | AEV |
| 00 04 040/0 | if Optioned | | . = |
| 02-B1-SWX2 | Step Well, CURBSIDE Entry Door, 2-Step Embossed Diamond Plate X | 1 | AEV |
| | Series | | |
| | (2) Steps : 9" Risers x 10" Tread on horizontal surfaces only | | |
| 05-IL-09X2 | < > ILOS Light, Step Well: 4" Kinequip #440206S, stainless steel | 1 | AEV |
| 03-1L-03X2 | housing LED | • | ALV |
| | Light shall come on with CS door or with right flood switch. | | |
| | | | |
| 05-IL-09XB | IATS Light, Step Well: 4" Kinequip #440206S, Stainless Steel | 1 | AEV |
| | surface mount LED | | |
| | Light shall come on with CS door or with right flood switch. | | |
| | | | |
| 02-BE-0105 | Entry Door Trimark Free Float Locking All Black Matte ILOS | | AEV |
| 02-BC-0502 | > Walk through, Cab Height, T1 Light Truck 2017 + Ford | 1 | AEV |
| 04-00-0900 | < > Threshold Transition Plate - Type I Install a transition plate at module interior, to protect belleve connection from module. | 1 | AEV |
| | Install a transition plate at module interior, to protect bellows connection from mo | auie | |
| | to cab. Material to be Aluminum. | | |
| 02-BD-0120 | > Body Drop: 6" Both Sides, Ahead of Rear Wheels | 1 | AEV |
| 02-X1-M149 | S > M-1 Compt (LF): 67.5" H x 22.125" W x 20.0" D | 1 | |
| 02-X1-W149 | S < Compartment Construction: STANDARD Diamond Plate | 1 | |
| 32 20 000Z | Sides and Back: .100 Polished Aluminum Diamond Plate | | / · V |
| | Compartment Ceiling: .090 Aluminum Sheet | | |
| | | | |
| | | | |
| | | | |

| 00/10/2023 | | Job/Order No. 220F 20430AA | 071/ | Page 4 |
|-------------|---|---|--------|--|
| PART NO | S | DESCRIPTION | QTY | ID |
| 02-B0-CC08 | | Compartment Door Panel: Diamond Plate | 1 | AEV |
| 12-DC-GA10 | | Compartment Finish: Diamond Plate Standard | 1 | AEV |
| 02-B0-CC16 | | Compartment Door Ventilation - small punched half-moon Louvered Door | 1 | AEV |
| | | | 1 | |
| 02-B0-SWFL | | Compt Floor: Sweep-out, even with bottom door jamb. | • | AEV |
| 02-B0-CC42 | S | | 1 | AEV |
| | | MTB to increase compartment floor thickness to .25 inch smooth aluminum. | | |
| | | | | |
| 02-BC-10A5 | | Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch | 1 | AEV |
| | | | - | |
| 02-B0-09B0 | | Compt Door Check: Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 02-BE-0110 | | Compartment Left -Single Door Handle Trimark All Black Matte ILOS | 1 | AEV |
| 05-EL-4T10 | | < Light, Cmpt: TecNiq E44 Strip Light, E44-W440-1 : Install - ILOS | 1 | AEV |
| | | MTB Note: No light hole required | - | |
| | | | | |
| | | Location: Light Strip to be installed on all sides (Except Bottom) | | |
| | | Strip length 198" maximum, Strip to be cut to length by manufacturing a | nd | |
| | | connectors installed. | | |
| | | | | |
| | | | | |
| 00 84 001 0 | | A Demonstrated MATABLE Description | , | A (T) (|
| 08-B1-02L2 | | Compartment M1 Wall Prep For 02 Lift | 1 | AEV |
| | | Build out back wall to 14" deep. | | |
| | | !!!!Make sure cmpt is at least 21.6" width minimum with a 10" cab extension to wor | k!!!!! | |
| | | | | |
| | | Final comments at interior Directorior valles well as well as included the 40 F/01 painting | | |
| | | Final compartment interior Dimension wall to wall minimum must be 18 5/8" minim | ım. | |
| | | | | |
| 09-ZZ-ZZZZ | | | 1 | AEV |
| 02-X1-M1AD | | > M-1A Comp (LF Upper):72 HR, 17.56" H x 22.125" W x 20.0" D | 1 | AEV |
| 02-B0-CC02 | | < Compartment Construction: STANDARD Diamond Plate | 1 | AEV |
| 02-00-0002 | | | | AL V |
| | | Sides and Back: .100 Polished Aluminum Diamond Plate | | |
| | | Compartment Ceiling: .090 Aluminum Sheet | l | |
| | | | | |
| 02-B0-CC08 | | Compartment Door Panel: Diamond Plate | 1 | AEV |
| | | | 1 | |
| 12-DC-GA10 | | Compartment Finish: Diamond Plate Standard | - | AEV |
| 02-B0-CC1B | S | > Compartment Ventilation - M-1A Pancake Fan | 1 | AEV |
| 02-B0-SWFL | | Compt Floor: Sweep-out, even with bottom door jamb. | 1 | AEV |
| 02-B0-CC41 | | > Compartment floor thickness .125" standard | 1 | AEV |
| 02-BC-10A0 | | Compartment Door: SINGLE DOOR, 1-point Latch | 1 | AEV |
| | | | | |
| 02-B0-09B0 | | Compt Door Check: Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 02-BE-0110 | | Compartment Left -Single Door Handle Trimark All Black Matte ILOS | 1 | AEV |
| 05-EL-4T10 | | < Light, Cmpt: TecNiq E44 Strip Light, E44-W440-1 : Install - ILOS | | AEV |
| 00 22 4110 | | MTB Note: No light hole required | • | 7120 |
| | | | | |
| | | Location: Light Strip to be installed on all sides (Except Bottom) | | |
| | | Strip length 198" maximum, Strip to be cut to length by manufacturing a | nd | |
| | | connectors installed. | | |
| | | | | |
| | | | | |
| 40 77 7777 | | | 4 | A (C) / |
| 12-ZZ-ZZZZ | | | | AEV |
| 02-X1-M275 | S | > M-2 Compt (LFM): 40.5" H x 49.875" W x 20.0" D | 1 | AEV |
| 02-B0-CC02 | | Compartment Construction: STANDARD Diamond Plate | 1 | AEV |
| 02 30 0002 | | Sides and Back: .100 Polished Aluminum Diamond Plate | | , <u>, , _ , , _ , , _ , , _ , , _ , , , ,</u> |
| | | | | |
| | | Compartment Ceiling: .090 Aluminum Sheet | | |
| | | | | |
| 02-B0-CC08 | | Compartment Door Panel: Diamond Plate | 1 | AEV |
| 12-DC-GA10 | | Compartment Finish: Diamond Plate Standard | 1 | AEV |
| 02-B0-SWFL | | Compt Floor: Sweep-out, even with bottom door jamb. | 1 | AEV |
| | | | - | |
| 02-B0-CC41 | | > Compartment floor thickness .125" standard | 1 | AEV |
| 02-B1-BIOX | | Bio-Waste: Diamond Plate Closeout for Bio in A/A | 1 | AEV |
| | | Dogleg for interior access bio-waste. | | |
| | | 17" W x 13"H and compartment depth less 2". | | |
| | | τι τι λ το τι απα σοπιραπιποπι ασμιποσο Ζ. | | |
| | | | | |
| | | | | |
| | | | | |

| 00/10/2023 | JOD/Order No. 220F 20430AA | OTV | Page 5 |
|--------------|--|------|--------|
| PART NO | S DESCRIPTION | QTY | ID |
| 02-B1-ELEC | < > Electrical Compartment : Circuit Board Storage within M-2 X series std. | 1 | AEV |
| | MTB >MIE 7215771 Mickey to build, and install 28" Welded enclosure comple | ete. | |
| | welded angled diamond plate compartment, Bottom hinged aluminum door w | | |
| | latch at top. Full width piano hinge at bottom. Small louver vents at top of door. I | | |
| | | DOOI | |
| | hinged at bottom. Single nader pin at top center, vertical. | | |
| | | | |
| | | | |
| 02-BC-10D0 | Doors, Compartment, DOUBLE DOORS (std) | 1 | AEV |
| 02-B0-09B0 | Compt Door Check: Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 04-TS-11D3 | | ' ' | AEV |
| | | | |
| 04-TS-4010 | Shelf Bracket: 90 Deg with Slotted Holes | 1 | AEV |
| 05-EL-4T10 | Light, Cmpt: TecNiq E44 Strip Light, E44-W440-1 : Install - ILOS | 1 | AEV |
| | MTB Note: No light hole required | | |
| | Location: Light Strip to be installed on all sides (Except Bottom) | | |
| | Strip length 198" maximum, Strip to be cut to length by manufacturing a | nd | |
| | | IIu | |
| | connectors installed. | | |
| | | | |
| | | | |
| 05-HA-13I6 | Condenser, 12V: ACC #25062, Dual Fan, Front of Module | 1 | AEV |
| | as part of HWP purchased for the medium duty units. | | |
| | | | |
| 04-HA-1311 | < > COOL BAR Front of Body, (5) - WARNING LIGHTS Pre-Drilled | 1 | AEV |
| 04 1111 1011 | #WEDGE-HVAC900 | | , · |
| | | /D 0 | |
| | Use of the wedge is subject to engineering review and approval for Light duty Ty | ype | |
| | III models. | | |
| | | | |
| 04-HA-1362 | Warning Lights installed on Condenser cover | 1 | AEV |
| 12-B0-0002 | Painted Part- Painted White YZ Std | 1 | AEV |
| 12-B0-0002 | Painted Part- Painted White YZ Std | 1 | AEV |
| 06-RR-13Z0 | Standard Conduit: 1-1/2"", with pull wire | 1 | AEV |
| 06-RR-13O4 | CONDUIT ORIGINATION POINT: M-2 compartment | 1 | AEV |
| | | | |
| 06-RR-13T3 | CONDUIT TERMINATION POINT: Behind A/A Board (Panel) | 1 | AEV |
| 06-RR-13Z1 | Conduit #2 1-1/2"" diameter, with pull wire, Type 1 units Std | 1 | AEV |
| 06-RR-13O1 | CONDUIT ORIGINATION POINT: Electrical Circuit board cabinet | 1 | AEV |
| 06-RR-13T2 | CONDUIT TERMINATION POINT: Behind Driver's seat | 1 | AEV |
| 09-ZZ-ZZZZ | I | 1 | AEV |
| 02-X1-M379 | ['] M-3 Compt (LR): 61.5" H x 25.0" W x 20.0" D | 1 | AEV |
| 02-B0-CC02 | - In Compartment Construction: STANDARD Diamond Plate | 1 | AEV |
| 02-D0-CC02 | | | ALV |
| | Sides and Back: .100 Polished Aluminum Diamond Plate | | |
| | Compartment Ceiling: .090 Aluminum Sheet | | |
| | | | |
| 02-B0-CC08 | Compartment Door Panel: Diamond Plate | 1 | AEV |
| 12-DC-GA10 | Compartment Finish: Diamond Plate Standard | 1 | AEV |
| 02-B0-SWFL | Compt Floor: Sweep-out, even with bottom door jamb. | 1 | AEV |
| 02-B0-CC41 | > Compartment floor thickness .125" standard | 1 | AEV |
| 02-BC-10A5 | Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch | 1 | AEV |
| 02-BC-10A3 | Compartment Boot: SiNGLE BOOK, Polward Imiged 2-point Laten | 4 | AEV |
| | | | |
| 04-EA-09B1 | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 04-TS-11C0 | > Shelf, Fixed, Ext: .188 smooth Aluminum, 2" Upward Lips | 1 | AEV |
| 04-TS-12ZS | < > Door Mounted Stair Chair Storage: for Stair chair mounting | 1 | AEV |
| | Requires reinforcement on door panel. | | |
| | Square trough at bottom of door panel, less width than door panel to allow for clos | ure | |
| | of door. | | |
| | , trim upper edge with Stampro rubber trim | | |
| | Install seatbelt restraint on door panel 20 inches up from inside bottom of trough. | | |
| | motali ocation restraint on door parior 20 mones up nom mote bottom of trough. | | |
| | | | |
| | | | |
| = | | | |
| 04-TS-12ZY | S > Mount Location: M3 Compartment | 1 | AEV |
| | | | |
| | | | |

| 08/18/2023 | | Job/Order No: 22OF 28438XA | | Page 6 |
|------------|------------|--|-----|--------|
| PART NO | S | DESCRIPTION | QTY | ID |
| 04-TS-STT3 | > | Strap: 2" Webb Cargo Belt 30-Inch long, adjustable ILOS | 1 | AEV |
| 04-TS-STR2 | | 2" Footman Loops: Locate back from jamb | 1 | AEV |
| 05-EL-4T10 | < | Light, Cmpt: TecNiq E44 Strip Light, E44-W440-1 : Install - ILOS | 1 | AEV |
| | | MTB Note: No light hole required | | |
| | | Location: Light Strip to be installed on all sides (Except Bottom) | | |
| | | Strip length 198" maximum, Strip to be cut to length by manufacturing a | nd | |
| | | connectors installed. | IIu | |
| | | connectors installed. | | |
| | | | | |
| | | | | |
| 09-ZZ-ZZZZ | _ | | 1 | AEV |
| 02-X1-M574 | S < | M-5 Compt (RR): 72 HR, 82.812" H x 10.5" W x 21." D | 1 | AEV |
| | | To make room for cabinets at head of SB with 2 drawers and pull | out | |
| | | sharp/trash | | |
| | | | | |
| 02-B0-CC02 | < | Compartment Construction: STANDARD Diamond Plate | 1 | AEV |
| | | Sides and Back: .100 Polished Aluminum Diamond Plate | | |
| | | Compartment Ceiling: .090 Aluminum Sheet | | |
| | | | | |
| 02-B0-CC08 | | Compartment Door Panel: Diamond Plate | 1 | AEV |
| 12-DC-GA10 | | Compartment Finish: Diamond Plate Standard | 1 | AEV |
| 02-B0-CC12 | < | Compartment Ventilation - Compartment Ceiling O O O O | 1 | AEV |
| 02-00-0012 | | | ' | ALV |
| | | MTB NOTE: hat channel with three (4") holes above the hat at the ceiling level. | | |
| | | | | |
| 00 00 0040 | | L. Oanne artenant Dane Vantilation and Harman had balk assemble assembly | , | A =\ / |
| 02-B0-CC16 | | Compartment Door Ventilation - small punched half-moon Louvered Door | 1 | AEV |
| 02-B0-SWFL | | Compt Floor: Sweep-out, even with bottom door jamb. | 1 | AEV |
| 02-B0-CC41 | > | The state of the s | 1 | AEV |
| 02-BC-10A5 | | Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch | 1 | AEV |
| 02-B0-09B0 | | Compt Door Check: Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 02-BE-0120 | > | Compartment Right -Single Door Handle Trimark All Black Matte | 1 | AEV |
| | | ILOS | | |
| 04-TS-STR1 | > | | 1 | AEV |
| | | ILOS | - | |
| 04-TS-STR2 | | 2" Footman Loops: Locate back from jamb | 1 | AEV |
| 05-EL-4T10 | < | Light, Cmpt: TecNiq E44 Strip Light, E44-W440-1 : Install - ILOS | 1 | |
| 00 LL 4110 | • | MTB Note: No light hole required | • | 7.27 |
| | | Location: Light Strip to be installed on all sides (Except Bottom) | | |
| | | | nd | |
| | | Strip length 198" maximum, Strip to be cut to length by manufacturing a | na | |
| | | connectors installed. | | |
| | | | | |
| 00 77 7777 | | | 4 | AEV |
| 09-ZZ-ZZZZ | • | | | |
| 02-X1-M675 | S > | M-6 Compt (RRFwd): 19.0" H x 17" W x 20.0" D | 1 | |
| 02-B0-CC02 | < | Compartment Construction: STANDARD Diamond Plate | 1 | AEV |
| | | Sides and Back: .100 Polished Aluminum Diamond Plate | | |
| | | Compartment Ceiling: .090 Aluminum Sheet | | |
| | | | | |
| 02-B0-CC08 | | Compartment Door Panel: Diamond Plate | 1 | AEV |
| 12-DC-GA10 | | Compartment Finish: Diamond Plate Standard | 1 | AEV |
| 02-B0-SWFL | | Compt Floor: Sweep-out, even with bottom door jamb. | 1 | AEV |
| 02-B0-CC41 | > | | 1 | AEV |
| 02-BC-10A0 | | Compartment Door: SINGLE DOOR, 1-point Latch | 1 | AEV |
| 02-B0-09B0 | | Compt Door Check: Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 02-BE-0120 | > | Compartment Right -Single Door Handle Trimark All Black Matte | 1 | |
| 02-DE-0120 | _ | ILOS | , | ~~ V |
| 05-EL-4T10 | < | Light, Cmpt: TecNiq E44 Strip Light, E44-W440-1 : Install - ILOS | 1 | AEV |
| 00-LL-4110 | | MTB Note: No light hole required | , | 7LV |
| | | Location: Light Strip to be installed on all sides (Except Bottom) | | |
| | | Strip length 198" maximum, Strip to be cut to length by manufacturing a | nd | |
| | | outp length 190 maximum, only to be out to length by maintacturing a | ııu | |
| | | | | |

| 08/18/2023 | | | Job/Order No: 22OF 28438XA | | Page 7 |
|-------------|---|-----|--|-----|----------------|
| PART NO | S | | DESCRIPTION | QTY | ID |
| | | C | connectors installed. | | |
| | | Ŭ | ormodere metanea. | | |
| | | | | | |
| | | | | | |
| 09-ZZ-ZZZZ | | | | 1 | AEV |
| 02-X1-M775 | S | < > | M-7 Compt (RF): 72 HR, 67.5" H x 17.25" W, I/O to ALS x 21" Deep | 1 | AEV |
| 02-X1-W110 | • | | | , | ALV |
| | | | Below Floor | | |
| | | T | o make room for cabinets at head of SB with 2 drawers and pull | out | |
| | | S | harp/trash | | |
| | | _ | | | |
| 00 00 4045 | | | L. Commenters and December (INIC) E. DOOD. Formand him and Our signal and | 4 | Λ Γ \ / |
| 02-BC-10A5 | | | Compartment Door: SINGLE DOOR, Forward hinged 2-point Latch | 1 | |
| 02-B0-09B0 | | | Compt Door Check: Double Action Gas Shock | 1 | AEV |
| 04-EA-09B1 | | | Door Swing Angle: Set to 90-100 degrees | 1 | AEV |
| 02-BE-0120 | | > | Compartment Right -Single Door Handle Trimark All Black Matte | 1 | AEV |
| OL-DL-0120 | | | | | 7.2 |
| | | | LOS | | |
| 05-EL-4T28 | | < | Light, Cmpt: TecNiq E44 Strip Light, E44-W12V-1, 54": Install IATS | 1 | AEV |
| | | I. | I/TB Note: No light hole required | | |
| | | | Part Number LITE-E44W12V1 | | |
| | | | | | |
| | | L | ocation: On compt jamb, Door Open side | | |
| | | | | | |
| | | | | | |
| 12-ZZ-ZZZZ | | | L. | 1 | AEV |
| | | | M 0 D= (DE): NONE D=#===== | - 1 | |
| 02-X1-M888 | | | M-8 Drawer (RF): NONE. Batteries Under Hood | 1 | AEV |
| 05-ZZ-ZZZZ | | | | 1 | AEV |
| 02-X1-RA02 | | > | Rear Access Doors: 46.75" Wide x 60.625" High | 1 | AEV |
| 02-BE-0170 | | | Rear Entry Doors Trimark Free Float All Black Matte ILOS | 1 | AEV |
| | | _ | | 1 | AEV |
| 09-IN-3STX | | < | Insulation: All Module Doors, 2" Black Foam, X-Series units | I . | AEV |
| | | # | FINSU-ARM2 | | |
| | | | | | |
| 09-IN-3STY | | < | Insulation: All Module Doors, Black Sound Proofing, X-Series units | 1 | AEV |
| 03-114-3011 | | | | | AL V |
| | | 77 | FINSU-KSU | | |
| | | | | | |
| | | | WELDING - CELL 1 | | AEV |
| 04-00-0009 | | > | Install Exterior Aluminum Parts with Rivets and Rivet Caps Optional | 1 | AEV |
| 04-AS-1800 | S | > | Stainless Steel - Sill protection: For the following compartments | 1 | AEV |
| | 3 | | | , | |
| 04-AS-18NA | | | M-1A: Left Front Compartment - Multiple Bend | 7 | AEV |
| 04-AS-18NC | | | M-1: Left Front Compartment - Multiple Bend | 1 | AEV |
| 04-AS-18NE | | > | M-2: Left Front Middle Compartment - Multiple Bend | 1 | AEV |
| 04-AS-18NG | | > | M-3: Left Rear Compartment - Multiple Bend | 1 | AEV |
| | | | | | |
| 04-AS-18NK | | > | M-5: Right Rear Compartment - Multiple Bend | 1 | AEV |
| 04-AS-18NM | | > | M-6: Right Rear Compartment - Multiple Bend | 1 | AEV |
| 04-AS-18NO | | > | M-7: Right Front Compartment - Multiple Bend | 1 | AEV |
| 04-AS-06A0 | | > E | Fuel Fill: CPI FG5301-1-238-U Open Housing, Polished Bezel - 53 degree (Std) | 1 | AEV |
| | | | | • | |
| 04-AS-0200 | | < | Fuel over Fill protection plate: Diamond plate | 1 | AEV |
| | | 1 | 2" Wide diamond plate shield shall be contoured to fit under the fuel filler housing | | |
| | | | | | |
| 04-AS-0801 | | 1 | Jrea Fill: CPI FG5301-1 Inlet Housing | 1 | AEV |
| | | | | | |
| 04-AS-0420 | | > | The second of th | 1 | AEV |
| 04-AS-0370 | | | Wire/Hose Cover : Diamond Plate, Between Cab & Module | 1 | AEV |
| 04-AS-0382 | | | Pass-Thru cab mounted wind deflector - Aluminum Diamond Plate | 1 | AEV |
| 04-BW-ABY1 | | < > | Bumper, Rear: X-Series 1/9 96" Wide w/ Embossed D/P Pontoon Covers | 1 | AEV |
| CI DII ADII | | | | | , \L v |
| | | ^ | (-Series Design. MTB; Delete std bumper. | | |
| | | | | | |
| 04-BW-FLIW | | < > | Step, Center:2" x 9" Bar Grate, flip-up, recessed | 1 | AEV |
| | | S | Standard with X series,> AEV builds | | |
| | | | MTB delete flip up step. | | |
| | | 11 | min doloto ilip up stop. | | |
| | | | | | |
| 04-EA-1306 | | | Dock Bumpers: Rubber D-Shape, 4" H x 18" W x 4" Thick X -series | 1 | |
| 04-BW-RF20 | | < > | Fenders, Rear: Rubber Extruded, Black | 1 | AEV |
| | | | MTB #7215439 | 1 | |
| | | 11 | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| • | | | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 8 |
|--------------|---|-----|----------------|
| PART NO S | DESCRIPTION | QTY | ID |
| 04-BW-DN00 | Corner Caps "X Series: | 1 | AEV |
| 04-BW-DN23 | < Front Corner Caps: 24.0" High, Alum Diamond Plate X Series | 1 | AEV |
| | Purchasing NOTE: Special Order from vendor. Delete standard rear corner ca | ps | |
| | from MTB | | |
| | If there is a body drop, add the appropriate height to Corner Caps. | | |
| | | | |
| 04-BW-DN33 | < > Rear Corner Caps: 24" High, Polished Diamond Plate, X-Series | | AEV |
| | Purchasing NOTE: Special Order from vendor. Delete standard rear corner ca | ps | |
| | from MTB | | |
| | If there is a body drop, add the appropriate height to Corner Caps. | | |
| | | | |
| 04-BW-DP2A | < > Rear Kick Plate: Aluminum D/P, Recessed, X-Series 96" wide STD Type 1 | 1 | AEV |
| | Delete standard rear kick-plate from MTB | | |
| | | | |
| | | | |
| 04-EA-2504 | Rear Recovery Eyes: (2) Cast Iron 2 9/16" center eye Black | 1 | AEV |
| 0. 27. 2001 | 1-3/16" ID center eye | - | , t_ v |
| | 1 6/10 1B oction eye | | |
| 04-EA-25A0 | Bezel with Access Door: For Tow Eyes CPI AD0001 No lock | 1 | AEV |
| 04-LA-23A0 | (2) #HOUS-10 | | ALV |
| | (2) #11003-10 | | |
| 04 DW TA02 | > Deceased Tax Areas Poliched Aluminum Diamond Plate | - 1 | AEV |
| 04-BW-TA03 | > Recessed Tag Area: Polished Aluminum Diamond Plate | | |
| 04-BW-TA04 | Location: Centered in the kick plate | 7 | AEV |
| 05-EL-44TO | Tag Lights: (2) Kinequip LED #132703C, ILOS | 7 | AEV |
| 05-EL-44XL | < Rear Flip up Step Lights, (2), Kinequip LED Strip light #KFL-SLC8 | 1 | AEV |
| | Mounted above rear bumper flip up step, in kick-plate recess | | |
| | | | |
| 04-BW-DP93 | < Front Stone Guards: 24.0" High, Alum Diamond Plate | 1 | AEV |
| | If there is a body drop, add the appropriate height to Stone Guards. | | |
| | | | |
| | | | |
| 04-BW-DPY9 | < > Skirt Rails: Polished D/P, w/ 12-inch LED Lights, X-series >> | 1 | AEV |
| | MTB, >Built by AEV | | |
| | | | |
| 05-EL-SKXB | < Skirt rail Lights, Front Pair 12" LED | 1 | AEV |
| | (1) Each side, forward position, in front skirt rail | | |
| | | | |
| 05-EL-SKV0 | < > (2) Skirt rail LED Strip Lights, Red/White 12" X-series | 1 | AEV |
| | NOTE: Mount Red On TOP and Clear on Bottom | | |
| | | | |
| 05-EL-SKXC | < Skirt rail Lights, Middle Pair 12" LED | 1 | AEV |
| 00 22 0.00 | (1) Each side, rear position, in front skirt rail | | , (L |
| | (1) Edon oldo, rodi pooldon, in none oldre rail | | |
| 05-EL-SKV0 | < > (2) Skirt rail LED Strip Lights, Red/White 12" X-series | 1 | AEV |
| OO LL OKVO | NOTE: Mount Red On TOP and Clear on Bottom | • | / \L V |
| | NOTE. Would Ned Oil TOI and Glear oil Bottoili | | |
| 05-EL-SKXD | < Skirt rail Lights, Rear Pair 12"-LED | 1 | AEV |
| UJ-LL-SKAD | | ' ' | ALV |
| | (1) Each side, in rear skirt rail | | |
| 05 51 61/1/0 | (0) Objet will ED Otain Limbte DestMARite 400 V and a | 4 | Λ Γ \ / |
| 05-EL-SKV0 | (2) Skirt rail LED Strip Lights, Red/White 12" X-series | 1 | AEV |
| | NOTE: Mount Red On TOP and Clear on Bottom | | |
| 05 EL 01/7: | | | A = \ / |
| 05-EL-SKZ1 | Skirt rail Lights Switched: Separate Switch in the Cab console | 1 | AEV |
| 05-EL-SLHX | LED Ground Lights: (6) Kinequip White 12" -LED lights, In Skirt rails x | 1 | AEV |
| 05-EL-SLGY | < LED Ground Lights Switched: | 1 | AEV |
| | The underbody lights work off a switch in the console or with any entry | or | |
| | compartment door. | | |
| | | | |
| 04-EA-09A0 | (2) Rear Door Hold Opens: Grabber Style, 1 on each door | 1 | AEV |
| 04-EA-14XF | > Running Boards: Embossed D/P, w/Bar Grate Insert, D/F(4) 12" lights X | 1 | AEV |
| | ILOS | | |
| | | | |
| | | | |

| 08/18/2023 | | | Job/Order No: 22OF 28438XA | | Page 9 |
|--------------------------|---|-----|--|-------|-------------------|
| PART NO | S | | DESCRIPTION | QTY | ID |
| 04-EA-1123 | | | Mud Flaps Front: Modular, Rubber, Dodge Type 1 | 1 | AEV |
| 04-EA-1132 | | | Mud Flaps Rear: Modular, Rubber AEV LOGO | 1 | AEV |
| 04-EA-1202 | | < | Heat plate above rear axle rise of exhaust, curbside | 1 | AEV |
| | | | AEV to install. | | |
| 05-EL-39X7 | | <> | Lights, Cab Step: 4" White LED, Surface mount box front, x series | 1 | AEV |
| | | | Surface Mount, In Chrome Flange. Wide body Units Only | | |
| | | | Activate by Cab Doors. Constant Hot. | | |
| | | | (2) Lite-2FLANGEC (2) LITE-20DCR | | |
| | | | (2) 2112 235 311 | | |
| 05-EL-SKV6 | | < > | (2) Skirt rail LED Strip Lights, Red/White 12" IATS NOTE: Mount Red On TOP and Clear on Bottom | 2 | AEV |
| 05-EL-SLJB | S | | LED Ground Lights: (2) Kinequip White 12" -LED lights, IATS | 2 | AEV |
| 05-EL-SLGY | 9 | < | LED Ground Lights Switched: | 2 | |
| 00-22-0201 | | | The underbody lights work off a switch in the console or with any entry | _ | 7124 |
| | | | compartment door. | | |
| | | | EXTERIOR LIGHTING / HEAT/AC / INSULATION - CELL 2 | | AEV |
| 05-HA-0800 | | _ \ | P Activ Tek induct 500-12V Dry H2O2 Air Purification -ozone free | 1 | AEV |
| 03-HA-0000 | | ` ' | System is to be installed in return airt Cabinet. Must be servicable, but not visib | | ALV |
| | | | EMT. >> Annual replacement of the UV bulb is required > | ie io | |
| | | | LIVIT. >> Attribution teplacement of the OV built is required > | | |
| 05-HA-0803 | | | Activ Tek system on while HVAC blower is running only. STD | 1 | AEV |
| 05-EA-3407 | S | < | | 1 | AEV |
| | | | To be Black coated by AEV | | |
| | | | TDK steel replacement bumper and grille guard, OEM bumper is removed a | nd | |
| | | | discarded. Front sensors mount behind bumper. | | |
| | | | This bumper for 2021 allows for Baja designs fog lights, purchased seperately. | | |
| | | | | | |
| 05-EL-1450 | | | Front Turn, Whelen M6 Series w/arrow, LED, Pair, IATS | 1 | AEV |
| 05-EL-1201 | | | Location: Front of Module, Below Light Bar | 1 | AEV |
| 05-PH-LF1B | | | M6 Series Flange, Black ILOS Each | 2 | AEV |
| 05-EL-1800 | | | CORNER CAP LED ICC/WARNING LIGHTS | 1 | AEV |
| 05-EL-18F0 | | | Front Corner Cap LED ICC/Warning Lights: Warnings RED/WHITE | 1 | AEV |
| 05-EL-18G8 | | < > | · · · · · · · · · · · · · · · · · · · | 1 | AEV |
| | | | ILOS | | |
| | | | Switch w/ Headlights. | | |
| 05-EL-18R5 | | | Rear Corner Cap LED ICC/Warning Lights: Warnings RED/AMBER | 1 | AEV |
| 05-EL-18S2 | | < > | | | AEV |
| | | | Switch w/ Headlights | | |
| 06 8W 6601 | | | L ICC Warring Limbte Cuitabade Drives and Only | 1 | Λ Γ\ / |
| 06-SW-CC01 05-EL-2503 | | | ICC Warning Lights Switched: Primary Only | 1 | AEV AEV |
| 05-EL-2503 | | < | LED Lights, Patient on Board, X-Series Units Install lights in the following locations: | 7 | AEV |
| | | | install lights in the following locations. | | |
| | | | M-1A Compartment - On Door panel, Outer lower corner | | |
| | | | M-1 Compartment - On Door panel, Outer Edge, Centered Top to Bottom | | |
| | | | M-2 Compartment - On Forward Door panel, Upper outer corner | | |
| | | | M-2 Compartment - On Trailing Door exterior, Upper outer corner | | |
| | | | M-3 Compartment - On Door panel, Outer Edge, Centered Top to Bottom | | |
| | | | M-5 Compartment - On Door panel, Outer Edge, Centered Top to Bottom | | |
| | | | M-6 Compartment - On Door panel, Outer lower corner | | |
| | | | M-7 Compartment - On Door panel, Outer Edge, Centered Top to Bottom | | |
| | | | C/S Entry Door - Below Center panel, Outer Edge | | |
| | | | Rear Entry Doors - (1) each door, Below Center panel, Outer Edge | | |
| | | | | | |
| | | | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 10 |
|--------------|--|-----|--------------|
| PART NO | | QTY | ID |
| | A Total of (11) Lights | | |
| | | | |
| | | | |
| | | | |
| | | | |
| 05-EL-252C | Red/White LED POB Light, Kinequip Each, X-Series Units | 11 | AEV |
| 05-EL-256X | Lights Switched with Entry Door Switch | | AEV |
| 05-EL-3252 | Fog Lights pair White , Whelen Nano 6 LED Flood lens with Black | 1 | AEV |
| 00-LL-3202 | housing NP6BB | , | ALV |
| | | | |
| | (2) LITE-NP6BB install the flood lens | | |
| | each light 3" tall x 3.5" wide | | |
| | Location: On top of Front Bumper or as possible to not block airflow | | |
| | White LED light | | |
| | Switch: Rocker Switch in cab console with legend. | | |
| | Each lite comes with a u-shaped bail bracket from Whelen. | | |
| | Edon ito contee with a a chapea ball bracket from vincion. | | |
| | | | |
| 05-EL-3254 | S < nano NP6BB 6LED recessed pan mounting bracket Black painted, | 1 | AEV |
| 05-EL-3254 | | , | ALV |
| | Pair, | | |
| | Paint BLACK | | |
| | need updated drawing, requested 10/24/17 | | |
| | A recessed pan with size to fit a Whelen Nano 6 LED light only. | | |
| | | | |
| | Potential install in aftermarket grille guard | | |
| | | | |
| 05-EL-3S10 | > Input Switching: Ignition/Battery Switch | 1 | AEV |
| 05-EL-33U4 | Driving or Fog Light to Cancel with OEM High Beam lights - | 1 | AEV |
| | Multiplex Elec system | | |
| 05-EL-42XX | TAIL LIGHTS | 1 | AEV |
| 05-EL-23X2 | > Tail Lights, Whelen LED Combinations , STD, X-Series | 1 | AEV |
| 05-EL-19MO | Fail Lights, Whelen LED Combinations, 31D, X-Genes Side Marker Lights: (2) RED Kinequip LED No 112401RD ILOS | 1 | AEV |
| 03-EL-19101O | | | ALV |
| | Switch w/ Headlights. | | |
| 05 51 0444 | 1. Marie Ma Octor Tellista | _ | 451/ |
| 05-EL-2414 | Whelen M6 Series, Tail Lights | 7 | AEV |
| 05-EL-2420 | Stop/Tail, Whelen M6 Series, LED, Pair RED LED/ RED LENS | 1 | AEV |
| 05-EL-2426 | > Turn, Whelen M6 Series, LED, Pair Amber LED, Amber LENS | 1 | AEV |
| 05-EL-2432 | > Back up, Whelen M6 Series, LED, Pair | 1 | AEV |
| 05-PH-LF2C | M6 Series Flange, Black ILOS Three Pair | 1 | AEV |
| 06-EC-4326 | Note: Standard Back-up Alarm Installed | 1 | AEV |
| 06-EC-4331 | Access Panel: NONE Required | 1 | AEV |
| 05-EL-43SM | < Third (3rd) Brake Light: RED LED, M6 Light | 1 | AEV |
| 03-LL-433W | LOCATION: Over Rear Access Doors. | | ALV |
| | | | |
| | Do not cut traditional hole. | | |
| | Just screw and wire holes required. | | |
| | | | |
| 05-EL-43T2 | Light is to steady burn, no flash | 1 | AEV |
| 05-PH-LF1B | M6 Series Flange, Black ILOS Each | 1 | AEV |
| 05-EL-4584 | > SCENE/FLOOD LIGHTS (LED-M9 Series) | 1 | AEV |
| 05-EL-46CH | Firetech Mini-Brow Lights 3 on Artic Wedge Group | 1 | AEV |
| 05-EL-46CJ | < > Front (2) FireTech Mini Brow Single Row FT-MB-9-S-W White | 1 | AEV |
| 00 22 4000 | housing 12" long | • | , . <u> </u> |
| | Lights will have end cap mounting brackets | | |
| | | | |
| | One light with Switch LEFT | | |
| | One light with switch RIGHT | | |
| A | | | 4 = - 1 |
| 05-EL-46CK | < > Front Center FireTech Mini Brow 15 LED Single row 20" Long White | 1 | AEV |
| | Light will have end cap mounting brackets | | |
| | One Switch/Icon For Center Brow Light | | |
| | | | |
| 05-EL-45LU | < > Left Scene Lights: (2) Whelen M9EZ-Black Flange ILOS | 1 | AEV |
| | ILLUMINATION -Instant | | |
| | | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 11 |
|--------------|--|-----|---------|
| PART NO | S DESCRIPTION | QTY | ID |
| | Power Setting-FULL | | |
| | | | |
| 06-EL-18LF | Left Flood Activate: Left Flood Switch | 1 | AEV |
| 05-EL-45TM | < > Right Scene Lights: (2) Whelen M9EZ-Black Flange ILOS | 1 | AEV |
| 00 22 401111 | ILLUMINATION -Instant | • | 7120 |
| | | | |
| | Power Setting-FULL | | |
| | | | |
| 06-EL-18RT | Right Flood Activate: Right Flood Switch and open CSE Door | 1 | AEV |
| 05-EL-46RM | < > Rear Load Lights: (2) Whelen M9EZ-Black Flange ILOS | 1 | AEV |
| | ILLUMINATION -Instant | | |
| | Power Setting-FULL | | |
| | . G | | |
| 06-EL-18RE | Activate: Rear Flood Switch, Reverse and Lead RA Door | 1 | AEV |
| | | _ | |
| 06-EL-1800 | Add Activation: Rearward Left and Right scene lights. come on w/ | 1 | AEV |
| | Reverse | | |
| 06-EL-SSQL | S <> IATS 12 volt Pioneer Surface Mount Spot/Flood Light Dual #PCPSM2B | 1 | AEV |
| | Black,(2) | | |
| | MTB, SURFACE MOUNT, corner mounting and wire hole only. | | |
| | | | |
| 05-PH-LT5F | Location:(1) Centered on each side of module | 1 | AEV |
| | | | |
| 06-EL-SSS7 | Switches Labeled: (1) Left Flood & (1) Right Flood | 7 | AEV |
| 05-HA-13XF | > HVAC SYSTEM: Max, Ducted in Ceiling - Above Walk-Thru Ford F | 1 | AEV |
| 05-HA-0406 | > Water Pump: Installed required | 1 | AEV |
| 05-HA-070X | > FILTER, Return Air: HEPA Merv-17 Horizontal 10" x 20" X series | 1 | AEV |
| 05-HA-1306 | A/C Condenser: See M2 Cmpt for Condenser Information | 1 | AEV |
| 05-HA-13X6 | > Intermotive Module BCVC502A :Installed 2020 + | 1 | AEV |
| 05-HA-14A0 | Side Plenum Grille, Return Air: Stamped Powder Coated Steel | 1 | AEV |
| | | • | |
| 05-HA-14C0 | > AC COMPRESSOR: Tee into OEM | 1 | AEV |
| 05-HB-14QX | AC Evaporator: MAXX w/ dual fans | 1 | AEV |
| 05-HA-1404 | Heater Hoses: EPDM - Nomex Rubber (per Ford QVM) | 1 | AEV |
| 05-HA-14A0 | Side Plenum Grille, Return Air: Stamped Powder Coated Steel | 1 | AEV |
| 05-HA-14B1 | Filter, Washable Carbon Pre-Filter | 1 | AEV |
| 10-HA-0304 | - Thermostat, Rear A/C, Digital, Class 1 LX-1, Includes Front Also | 1 | AEV |
| 10-11/4-0304 | Thermostat located in A/A | | ALV |
| | mermostat located in A/A | | |
| | | | |
| | | | |
| 05-IL-00X1 | > Ceiling Panels; white Aluminum Composite (2) piece X series | 1 | AEV |
| 05-IL-01XR | < > Dome Lts, LED "LIGHT RAIL" 7' 6" system White LED, Red LED X -Series | 1 | AEV |
| | MTB NOTE: Requires X-Series Roof Structure design | | |
| | | | |
| 05-IL-05T5 | < Check out Light Switch:(2) Momentary For Multi-plex electrical | 1 | AEV |
| 03-1L-0313 | , | , | ALV |
| | systems. | | |
| | (1) At RF ALS | | |
| | (1) on rear door | | |
| | switches to activate the checkout timer | | |
| | | | |
| 05-IL-05T1 | < > Timer, Constant Hot, Check out, Class 1 Multiplex System | 1 | AEV |
| 00 12 0011 | Activated with opening of either C/S or Rear Entry Doors. | | / \L V |
| | Activated with opening of either 6/3 of Near Entry Doors. | | |
| 00 50 0044 | | | A =\ / |
| 06-EC-0914 | < 15 Minute Activation | 1 | AEV |
| | Light Circuit to stay on for 15 minutes when entry door is opened. | | |
| | | | |
| 06-EC-09P3 | S > Timer to Power: CENTER LIGHT RAIL | 1 | AEV |
| ZZ-ZZ-ZZZZ | | 1 | AEV |
| 06-RR-0700 | (2) Speakers: Stereo, patient compartment, in center pad | 1 | AEV |
| | | 1 | |
| 10-RR-0600 | Volume Control, Stereo: in A/A, For Rear speakers | 1 | AEV |
| 09-MH-0801 | > IV Hook No 1: CPI Rubber IV 2008-1(Recessed Mount), ILOS | 1 | AEV |
| 29-MH-1000 | LOCATION: Over head/chest area, primary patient on COT | 1 | AEV |
| 09-MH-0802 | IV Hook No 2: CPI Rubber IV 2008-1(Recessed Mount), ILOS | 1 | AEV |
| 09-MH-08P2 | LOCATION: OH /chest area, secondary patient on S/B | 1 | AEV |
| | | | |
| | | | |
| | | | |

| 08/18/2023 | S DESCRIPTION | OTV | Page 12 |
|--------------------------|--|----------|-------------------|
| PART NO 09-MH-2AC5 | S DESCRIPTION > Recessed C/S Grab Rail, ceiling: 1.25 Dia 3 pt, 72in, Gray Anti microbial | QTY 1 | ID AEV |
| 09-WII 1-2A03 | Necessed 6/6 Grab Nail, ceiling. 1.25 Dia 5 pt, 72iii, Gray Anti microbiai | | ALV |
| 09-MH-2ASX | < > Recessed S/S Grab Rail, ceiling: 1.25 Dia S/S, 3 pt, 72in, Gray X-series | 1 | AEV |
| | Grab Rail will be recessed in a ABS pan. | | |
| | | | |
| | luculation DKO. V Ocales audits | | A = \ / |
| 05-IN-3STX | > Insulation PKG: X-Series units < I Insulation: All Module Doors. 2" Black Foam, X-Series units | 1 | AEV AEV |
| 05-1N-551X | Insulation: All Module Doors, 2" Black Foam, X-Series units #INSU-ARM2 | ı | ALV |
| | #INOU-AINIZ | | |
| 05-IN-3STY | Insulation: All Module Doors, Black Sound Proofing, X-Series units | 1 | AEV |
| | #INSU-KSU | | |
| | | | |
| 05-IN-4ST9 | > Insulation Sound Deadening: Generation 9 Floor | 1 | AEV |
| 05-IN-5STX | < > Insulation: Walls/Ceiling, 1" Black Foam, X-Series units | 1 | AEV |
| | #INSU-ARM1 | | |
| 05-IN-6STX | < > Stepwell Insulation: Urethane Froth Insulation, STD X-Series units | 1 | AEV |
| 00-114-0017 | MTB #7208738 | | ALV |
| | W15 W1200100 | | |
| | | | |
| 05-IN-6SXS | < > Black Sound Proofing, Doors & Select Walls, X-Series units | 1 | AEV |
| | INSU-KSU | | |
| 05 IN 00VT | | 4 | A = \ / |
| 05-IN-6SXT | Insulation: Circumferential PKG, 1LEF Reflective, X-Series units #KSU-F1250 | 1 | AEV |
| | #K5U-F1250 | | |
| 05-LB-6240 | Front of Module M Series LED System - 92" and wider | 1 | AEV |
| 05-PM-LT03 | Light: Whelen M9, LED, WHITE LED/CLEAR Lens, Programmable | 2 | AEV |
| | iats | | |
| 05-EL-020Y | Flange: (1) Black Flange for above M9 light | 2 | AEV |
| 05-PM-LT05 | Light: Whelen M9, LED, RED LED/CLEAR Lens, Programmable iats | 2 | AEV |
| 05 EL 020V | Flance (4) Block Flance for above MO limbs | 2 | A = \/ |
| 05-EL-020Y 05-LB-6900 | Flange: (1) Black Flange for above M9 light Alternative Lightbar Switching, Prim/Sec | 2 | AEV AEV |
| 03-LB-0900 | Module Rear Chevron Warning Light Systems | • | AEV |
| 05-Q0-0010 | Rear Chevron Warning Top Pair 1 | 1 | AEV |
| 05-Q0-0100 | > Red LED Whelen PSR01FCR, clear lens Strip light plus solo | 2 | AEV |
| 05-Q0-0132 | S < Install Black Flange | 2 | AEV |
| | Install Lights in Between Chevrons | | |
| 05 00 0040 | L. D Ol W i D. i . O | 4 | 4517 |
| 05-Q0-0012 05-Q0-0100 | Rear Chevron Warning Pair 2 Red LED Whelen PSR01FCR, clear lens Strip light plus solo | 1 | AEV AEV |
| 05-Q0-0132 | S < Install Black Flange | 2 | AEV |
| 00-00-0132 | Install Lights in Between Chevrons | _ | ALV |
| | | | |
| 05-Q0-0014 | Rear Chevron Warning Middle Pair 3 | 1 | AEV |
| 05-Q0-0100 | > Red LED Whelen PSR01FCR, clear lens Strip light plus solo | 2 | AEV |
| 05-Q0-0132 | S < Install Black Flange | 2 | AEV |
| | Install Lights in Between Chevrons | | |
| 05-Q0-0016 | Rear Chevron Warning Pair 4 | 1 | AEV |
| 05-Q0-0110 | > Red LED Whelen PSR01FCR, clear lens Strip light plus solo | 2 | AEV |
| 05-Q0-0132 | S < Install Black Flange | 2 | AEV |
| | Install Lights in Between Chevrons | | |
| | | | |
| 05-Q0-0018 | Rear Chevron Warning Bottom Pair 5 | 1 | AEV |
| 05-Q0-0130 | > Amber LED Whelen PSA01FCR, Clear lens Strip light Plus Solo | 2 | AEV |
| 05-Q0-0132 | S Install Black Flange | 2 | AEV AEV |
| 05-Q0-0300 | < > Chevron Rear Amber Turn Signal Option. Set rear Amber Chevron Strip Lights to Steady Burn, Use Additional Flasher, for T | | AEV |
| | Secretal Airiber Orievion Strip Lights to Steady Durin, Ose Additional Flasher, 101 | uiii | |
| | | | |

| 08/18/2023 | | Job/Order No: 22OF 28438XA | | Page 13 |
|----------------|---|---|-----|---------|
| PART NO | S | DESCRIPTION | QTY | ID |
| | | signal. | | |
| | | This item does not replace any turn signal light package, | | |
| | | The Rem does not replace any turn signal light package, | | |
| 05-Q0-0315 | c | Proke Light Overvide, Wire into year warning lights chave | 1 | AEV |
| 05-Q0-0315 | S | | 7 | AEV |
| | | Includes FLAS-ULF44 (1) | | |
| | | Flasher unit to flash lights during warning cycle | | |
| | | Red Chevron Lights to Have Brake Override. | | |
| | | | | |
| 06-EL-2501 | | Override Function: During ALL modes of operation | 1 | AEV |
| 05-SY-LTMF | | > M SERIES LED WARNING LT SYSTEM - F-series LTD | 1 | AEV |
| 05-FS-0712 | | | 1 | AEV |
| | | Flasher: None, All M Series LED's Are Programmable | 1 | |
| 05-FS-10P4 | | Flash Pattern: None, Internal Light Head Flasher | 1 | AEV |
| 06-SW-PS01 | | Warning Light SWITCH: center console, Primary / Secondary | 1 | AEV |
| 05-PM-LC06 | | (4) Grille Lights: Whelen M2 Series, LED F series | 1 | AEV |
| 05-PM-LN07 | | Flanges,(2) Black: Whelen M2 M2FB | 2 | AEV |
| 05-PM-LRC6 | S | Lights: (2) Whelen M2, LED, RED LED/CLEAR Lens Programmable | 1 | AEV |
| 00 1 111 21100 | | llos | - | 71_0 |
| 05-PM-LRCC | S | Light: Whelen M2, LED, CLEAR LED/CLEAR Lens Pair IATS | 1 | AEV |
| | 3 | | - | |
| 05-PM-LE09 | | (2) Intersection Lights: Whelen M2 Series, LED | 1 | AEV |
| 05-PM-LN07 | | Flanges,(2) Black: Whelen M2 M2FB | 1 | AEV |
| 05-PM-LRC6 | S | Lights: (2) Whelen M2, LED, RED LED/CLEAR Lens Programmable | 1 | AEV |
| | | llos | | |
| 05-PM-LF70 | | (1) Center Front Body Light: Whelen M9 Series, LED | 1 | AEV |
| 05-PH-LF02 | | M9 Series Flange, Black, ILOS Each | 1 | AEV |
| 05-PM-LRK1 | | Light: Whelen M9, LED, WHITE LED/CLEAR Lens, Programmable | 1 | AEV |
| US-FIVI-LKKI | | | , | ALV |
| | | ea ilos | | |
| 05-PM-LG70 | | (2) Outer Front Body Lights: Whelen M9 Series, LED | 1 | AEV |
| 05-PH-LF04 | | M9 Series Flange Black Pair | 1 | AEV |
| 05-PM-LRK3 | | Light: Whelen M9, LED, RED LED/CLEAR Lens, Programmable | 2 | AEV |
| | | ILOS | | |
| 05-PM-LH70 | | (4) Upper Side Body Lights: Whelen M9 Series, LED | 1 | AEV |
| 05-PH-LF06 | | M9 Series Flange, Black Two Pair | 1 | AEV |
| | | | 1 | |
| 05-PM-LRK3 | | Light: Whelen M9, LED, RED LED/CLEAR Lens, Programmable | 4 | AEV |
| | | ILOS | | |
| 05-PM-LI09 | | (2) Rear Intersection Lights: Whelen M2 Series, LED | 1 | AEV |
| 05-PM-LN07 | | Flanges,(2) Black: Whelen M2 M2FB | 1 | AEV |
| 05-PM-LRC8 | | > Light:s Whelen M2, LED, RED LED/CLEAR Lens PAIR -flash IATS | 2 | AEV |
| 05-PM-LJ70 | | (2) Outer Rear Body Lights: Whelen M9 Series, LED | 1 | AEV |
| 05-PH-LF04 | | M9 Series Flange Black Pair | 1 | AEV |
| 05-PM-LRK3 | | Light: Whelen M9, LED, RED LED/CLEAR Lens, Programmable | 2 | AEV |
| US-FIVI-LKKS | | | 2 | ALV |
| | | ILOS | | |
| 05-PM-LK70 | S | (4) Additional Rear Body Lights: Whelen M9 Series, LED | 1 | |
| 05-PH-LT6B | S | | 1 | AEV |
| | | 1 Set Located Above Rear Doors See Drawing | | |
| | | · | | |
| 05-PM-LT05 | S | Light: Whelen M9, LED, RED LED/CLEAR Lens, Programmable iats | 4 | AEV |
| 05-EL-020Y | S | Flange: (1) Black Flange for above M9 light | 1 | AEV |
| | J | | 1 | |
| 05-PM-LL30 | | (1) Center Rear Body Light: Whelen M6 Series, LED ILOS | 7 | AEV |
| 05-PH-LF1B | | M6 Series Flange, Black ILOS Each | 1 | AEV |
| 05-PM-LRG7 | | Light: Whelen M6, LED, AMBER LED/CLEAR Lens, Flash, ILOS | 1 | AEV |
| 05-PN-KPM6 | | Additional Warning Lts : (2) Whelen M6 Lights | 1 | AEV |
| | | | | |
| | | | | |
| | | | | |
| 05-PH-LF1B | | M6 Series Flange, Black ILOS Each | 2 | AEV |
| | | | 2 | |
| 05-PM-LRG1 | | Light: Whelen M6, LED, WHITE LED/CLEAR Lens, Program ILOS | 2 | AEV |
| 05-PS-LC63 | | < Location: On REAR Kick plate, (1) each side | 1 | AEV |
| | | Below tail lights, on rear of module | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

| 08/18/2023 | | Job/Order No: 22OF 28438XA | | Page 14 |
|--------------|---|--|-------|---------|
| PART NO | S | DESCRIPTION | QTY | ID |
| 05-ZZ-ZZZZ | | | 1 | AEV |
| | | ELECTRICAL - CELL 3 | | AEV |
| 05-IL-12MT | | > Cab Ovhd Lights: Pair, Whelen 60CREGCS Red/White LED 6-inch | 1 | |
| 06-00-0004 | | < Customer Supplied Part(s) : NONE | 1 | |
| 00-00-0004 | | ITEMS MUST BE NEW, No USED items accepted. Required under GSA-K-18 | | ALV |
| | | , | 122 | |
| | | and CAAS GVS. | | |
| | | | | |
| 06-00-0053 | | < > Tremco Ignition Security Kit -Ford F series all models 150-650-Current | 1 | AEV |
| | | Plug and play kit, | | |
| | | Includes hardwired main disconnect switch on harness, air bladder type switch. | | |
| | | | | |
| | | | | |
| 05-IL-1005 | S | < > Rechargeable Flash Lt: Streamlight, SL40 Orange, | 2 | AEV |
| 00 12 1000 | | SHIP LOOSE FLASHLIGHTS DO NOT INSTALL | | 7.2. |
| | | SHIF LOOSE I LASHLIGHTS DO NOT INSTALL | | |
| 05 11 401 0 | _ | L. Landian, DDE MIDE DEUND ACCESS DANEL IN M.A. | _ | 451 |
| 05-IL-10L3 | S | Location: PRE-WIRE BEHIND ACCESS PANEL IN M-1 | 2 | |
| 05-IL-10P0 | | Powered: 12v Constant Hot | 2 | |
| 06-AM-SAH5 | | < > AEV Trauma Hawk Telematics System - T1,3 AEV RMR-LX1 etc Ford | 1 | AEV |
| | | Vehicles | | |
| | | AEV remote vehicle monitoring Gen 3 system Telematics (Most AEV Elect | rical | |
| | | systems) | | |
| | | Antenna to be mounted on chassis cab roof, | | |
| | | 12 months of subscription software licence included in purchase. | | |
| | | one speaker in chassis cab SPEA-SH8O, in console, | | |
| | | | | |
| | | Driver ID Fob reader installed on front console | | |
| | | Includes (5) ID-FOBS for driver identification (ship with vehicle), WIRE TIE to | | |
| | | fobs to the Acetech system for the customer to remove at comissioning of the veh | icle. | |
| | | | | |
| 06-AM-SAL1 | | Location: Behind Passenger seat | 1 | AEV |
| 06-RR-0707 | | > (1) Speaker: Connect to AEV Traumahawk Telematics in ACTION | 1 | AEV |
| | | AREA | | |
| 06-BA-3F41 | | Batteries: 2 - Battery System - Type I Diesel only | 1 | AEV |
| 06-BA-3F53 | | Batteries: (2) Underhood (Type I) | 1 | |
| 06-BA-3FJ1 | | Battery Make: (2) OEM | 1 | |
| 00-DA-31 3 1 | | | | AL V |
| | | Battery Brand must match. | | |
| 00 DA 0004 | | 1 B # 0 # 1 O I II | | A => / |
| 06-BA-Q631 | | < > Battery Switch: Cole Hersee 2484-16 Paddle, T1 center console | 1 | AEV |
| | | SWITCH LOCATION: Drivers' side of center cab console. | | |
| | | | | |
| 06-BA-3FW4 | | Batteries Wired: Parallel for higher amperage | 1 | AEV |
| 06-EC-056C | | > POWER Door Locks: Module Doors, X-Series Units type 1 Ford | 1 | AEV |
| 06-EC-050B | | Door Locks, Tied into OEM System X series Type 1 Ford | 1 | AEV |
| | | Module power locks are tied to the Chassis power lock system | | |
| | | MDUL-BDLM506A Module door lock control F3/4/550 | | |
| | | WIDGE-BELVISOON WOULD GOT TOOK CONTROL 1947000 | | |
| 06-EC-0512 | | OCAN Kay Fahr Individed WiChessie Unlack Med Dears | 1 | AEV |
| 00-EC-0512 | | < OEM Key Fob: Included w/Chassis Unlock Mod Doors | 1 | AEV |
| | | Must also operate the Module Power Door Locks Optioned. | | |
| | | | | |
| 06-EC-05B9 | | Door Lock Switches : Integrated in Interior Entry door Handles -x | 1 | |
| 06-EC-05M0 | | ONLY the following doors shall have power door locks: | 1 | AEV |
| 06-EC-05X0 | | Electric Door Lock: (M-1A) Upper Left Front Compartment, | 1 | AEV |
| 06-EC-05X1 | | Electric Door Lock: (M-1) Left Front Compartment | 1 | AEV |
| 06-EC-05X2 | | Electric Door Lock: (M-2) Left Middle Compartment | 1 | AEV |
| 06-EC-05X4 | | Electric Door Lock: (M-2) Left Rear Compartment | 1 | AEV |
| 06-EC-05X4 | | I Electric Door Lock: (M-3) Left Real Compartment | 1 | AEV |
| | | | | |
| 06-EC-05X7 | | Electric Door Lock: (M-5) Right Rear Compartment | 1 | AEV |
| 06-EC-05X9 | | Electric Door Lock: (M-6) Right Rear, Forward Compt | 1 | AEV |
| 06-EC-05XA | | Electric Door Lock: Curbside Access Door | 1 | AEV |
| 06-EC-05XB | | Electric Door Lock: (M-7) Right Front Compt | 1 | AEV |
| 06-EC-081X | | Remote Keypad #1: Installed, Horizontal X-Series Units | 1 | AEV |
| | | MTB to cut mounting holes per provided drawing. | | |
| | | | | |
| | | | 1 | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 15 |
|----------------|--|-----|--------------|
| PART NO | S DESCRIPTION | QTY | ID |
| | | | |
| | | | |
| 06-EC-0816 | Location: By Curbside Door | 1 | AEV |
| 06-EC-281X | Door Unlock Switch, Momentary, Exterior, hidden : NONE | 1 | AEV |
| 06-EC-3001 | < > Backeye 360 4 camera Displays into multiplex system - Brigade | | AEV |
| | Brigade select 360 system without front monitor display | | / |
| | (1) rear camera mounted up high | | |
| | (1) front camera mount on front grille | | |
| | (1) from carriera friount of from grille (1) camera on each side of vehicle just forward of mid point with cover. | | |
| | | | |
| | system displays into multiplexing front display purchased separately. | | |
| | this item with Domestic USA warranty | | |
| | | | |
| 06-EC-3204 | < Monitor: Display through Electrical system information screen Front | | AEV |
| | Contents of camera(s) to display as needed onto electrical system main screen | า. | |
| | Available for Weldon V-mux, REV VX-1 and REV LX-1 | | |
| | | | |
| 12-B0-0004 | Painted Part- Painted Special color to match Body | | AEV |
| 06-EC-4300 | > Back-up Alarm: Standard 102DB | | AEV |
| 06-EC-43C0 | Cut Off Switch: NONE | | AEV |
| 06-EC-CCX2 | S <> Circuit Board, 12V: Multiplex LX1 F3/4/550 X-Series STD | 1 | AEV |
| | Includes the Following Items, | | |
| | Rear Digital Thermostat/Control for A/C, includes front also | | |
| | 5-minute shutdown timer std. | | |
| | Door Open 15, minute check out timer | | |
| | Oxygen Contents Gauge front and back. | | |
| | (5) Minute Auto Battery Switch Shutdown (Kill Circuit) | | |
| | · · · · · · · · · · · · · · · · · · · | | |
| | | | |
| 06-EC-1304 | Voltage Monitor, LX-1, w/ Warning Light | 1 | AEV |
| 06-EC-2215 | LX-1 Standard Module door Open Alarm and Icon on Front Display | 1 | AEV |
| 06-EC-CB07 | > Circuit Protection, 12V: FET - Auto-reset | | AEV |
| 06-EC-SPAF | < > LX1 Main Switch Panel Location : Front Display 12-inch full color w | | AEV |
| 00 20 01 711 | buttons ILOS | | / L_ V |
| | Full Touch Screen, no buttons. Real Time Clock, IP67 sealed | | |
| | UV1200 | | |
| | O V 1233 | | |
| 06-EC-SPA8 | In Cab Console | 1 | AEV |
| 06-FS-1106 | > Sequencer, LX1, with load manager, | 1 | AEV |
| 06-RR-A004 | > Type I - CAB Aluminum Black Speed liner 14" OAW Modular design 2023+ | 1 | |
| 00 141 17100 1 | WEDGE | | , ·_ · |
| 06-MC-0110 | > Engine Hour meter: OEM, Gauge Cluster | 1 | AEV |
| 06-RR-A100 | Aluminum-Black Speedliner Wedge for LX-1 | | AEV |
| 07-RR-0216 | > Add-on Console: Type 1 CONS-ADDON-3 Alum Modular Black 2- | | AEV |
| 07-1414-0210 | opening | | ALV |
| 07-RR-02B3 | Drink Holder: (2) In Add-on Console, Big Gulp Alum Mod System | 1 | AEV |
| 07-KK-02D3 | Dillik Holder. (2) III Add-olf Collsole, Dig Gulp Alulii illod System | | ALV |
| | | | |
| | | | |
| 07-RR-02A5 | Drink Holder Location: Front | 1 | AEV |
| 07-RR-02C3 | Note Book slot divider -Alum Spray-Coated Black Each | | AEV |
| 07-RR-0512 | > Armrests, Padded: Adjustable Height Pair, Black | 1 | AEV |
| 07-ZZ-ZZZZ | Anniests, r added. Adjustable Height r all, black | - | AEV |
| 07-RR-24A7 | Wire Harness Cover installed Behind Driver's Seat ILOS | | AEV |
| 37-141-24A1 | 22 inch long COVE-LOOM aluminum with Black textured powder coat cover installe | | ~ - ₹ |
| | over harness. | u | |
| | Over namess. | | |
| 07-ZZ-ZZZ | | 1 | AEV |
| 06-EC-GR01 | > Ground Straps, Module to Frame: (Qty 4) Braided | | AEV |
| 06-EC-SP71 | S 2nd patient area switch panel mounted on angled cabinet | | AEV |
| 06-EC-SP91 | XS <> 1st Pt Area LX-1 Switch Panel Special Ultra View UV800 PCAp with 10 | | AEV |
| 00-EC-3P91 | • | T | AEV |
| | button ligh | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | 0=1/ | Page 16 |
|--------------|---|--------|-------------------|
| PART NO | | QTY | ID |
| | Install PANL-UV800 1 (610-00060-080-ST) 7 inch full color display, no extended buttons. Full touch-screen readable through gloves and mist. Sunligi | | |
| | readable, IP67 sealed. | 11. | |
| | readable, iror sealed. | | |
| | Return standard front console PANL-BP2070 7 inch with buttons LX-1 panel t | to | |
| | parts room for restock and credit. | | |
| | parte room for rootook and oroans | | |
| 06-EC-SPA8 | S A/A | 1 | AEV |
| 06-EC-SPZ0 | S < Patient Area LX1 Panel: | 1 | AEV |
| | Install PANL-UV800 1 (610-00060-080-ST) 7 inch full color display, no ext | ra | |
| | buttons. FullI touch-screen readable through gloves and mist. Sunligi | ht | |
| | readable, IP67 sealed. | | |
| | | | |
| | Return standard front console PANL-BP2070 7 inch with buttons LX-1 panel to | iO | |
| | parts room for restock and credit. | | |
| 06-EC-SPZ5 | U 2nd Pt Area LX-1 Switch Panel, UV800 with 10 Smart Switches IATS | | |
| 06-IA-0001 | U 2nd Pt Area LX-1 Switch Panel, UV800 with 10 Smart Switches IATS Converter, 125V to 12V: NONE | 1 1 | AEV |
| 06-IG-0250 | > Inverter: Vanner LIFESINE 1100 Pure Sine Wave, w 55watt 3 stage charger | 1 | AEV |
| 06-EC-03AS | Portable Equip Charging Circuits: Included in Inverter | 1 | AEV |
| 06-EC-03AA | PREWIRE LOCATION: (1) Cab Console, (1) Behind A/A | 1 | AEV |
| 06-EC-03C9 | > Portable Equip Pwr Source: Ignition and/or Shoreline | 1 | AEV |
| 06-IG-03A0 | Battery Charger/Conditioner: 55A - Built into Inverter | 1 | AEV |
| 06-IG-0003 | Built-in Battery Charger: Enable - Wire to Batteries | 1 | AEV |
| 06-IG-04L7 | Inverter Location: M-1A (ULF) Compartment | 1 | AEV |
| 06-MC-0901 | Low Voltage Buzzer: Installed, Multiplex units | 1 | AEV |
| | COMMUNICATION RADIO(S) RELATED | | AEV |
| | RADIO POWER | | AEV |
| 06-EC-03A0 | Radio Power No 1: 30A, Pos and Neg, 10 awg Wires | 1 | AEV |
| 06-EC-03B0 | Radio Power Source: Battery Switch Hot | 1 | AEV |
| 06-EC-03G0 | LOCATION: Behind Passenger's Seat | 1 | AEV |
| 06-EC-03A2 | Radio Power No 2: 30A, Pos and Neg, 10 awg Wires | 1 | AEV |
| 06-EC-03B0 | Radio Power Source: Battery Switch Hot | 1 | AEV |
| 06-EC-03E0 | LOCATION: Behind Action Area Board ANTENNA LEADS | 1 | AEV AEV |
| 06-RR-1710 | ANTENNA LEADS Antenna Base w/ Coaxial Cable: KE794 #1 | 1 | AEV |
| 00-101-17-10 | MOUN-KE794 | ' | ALV |
| | INIOGIVILLI GI | | |
| | | | |
| 06-RR-01P0 | Port Plate: None - Access thru center upholstery panel | 1 | AEV |
| 06-RR-1760 | < Roof Location: Roof Port #1 | 1 | AEV |
| | MOUN-K794 | | |
| | Line up with edge of curbside entry door, centered side to side as near as possible. | | |
| | | | |
| 06 DD 4776 | Townshootion Points Incide Add On Concells | 4 | A =\/ |
| 06-RR-1776 | < > Termination Point: Inside Add On Console MOUN-K794 | 7 | AEV |
| | IVIOUN-R794 | | |
| | | | |
| 06-RR-1712 | < Antenna Base w/ Coaxial Cable: KE794 #2 | 1 | AEV |
| | MOUN-KE794 | | |
| | | | |
| | | | |
| 06-RR-01O2 | < ORIGINATION POINT: Roof Port No 2 | 1 | AEV |
| | Roof Port No 2 is located approximately 24 inches back rearward of roof port #1. | | |
| 00 00 0100 | I David Dieder Marco Access the constant of the | | A = 1 / |
| 06-RR-01P0 | Port Plate: None - Access thru center upholstery panel | 1 | AEV |
| 06-RR-1774 | < Termination Point: Behind A/A Board MOUN-K794 | 7 | AEV |
| | IVIOUN-N/94 | | |
| | | | |
| | | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 17 |
|------------|---|-----------|---------|
| PART NO | S DESCRIPTION | QTY | ID |
| 06-RR-1809 | Patient Area Radio : None | 1 | AEV |
| 06-SO-0000 | 125V SHORE LINE AND OUTLETS | 1 | AEV |
| 06-SO-0500 | < > Shore Line Inlet: 20A Super Auto Eject, ILOS | 1 | AEV |
| | >> Access plate either interior or exterior mounting plate required << | - | 7 .— 1 |
| | >> Access plate either interior or exterior mounting plate required ** | | |
| 06-SO-00L1 | Inlet location: Aft of Left Front compartment | 1 | AEV |
| 06-SO-0805 | Indicator Light, Shore line: Weather proof, power by SL, Red | 1 | AEV |
| 00-30-0003 | | | ALV |
| | Indicator light located above shore line inlet. | | |
| 06-SO-1027 | Cover, Black Shore Line Inlet : 20A Super Auto Eject, ILOS | 1 | AEV |
| 06-SO-10TT | Inpower Timer: VCM-05-01SF, Installed | 1 | AEV |
| 00-30-1011 | | , i.e. a. | ALV |
| | NOTE: This allows the auto eject to be wired to the ignition switch In lieu of splice | ang | |
| | into the OEM starter circuit and is required any this vehicle | | |
| | | | |
| | | | |
| 00 00 4400 | L ************************************ | | A =\ / |
| 06-SO-1400 | **125 Volt OUTLETS** | 1 | AEV |
| 06-SO-1460 | < > 125 VAC Quad Outlet 1;15A, Lighted Hospital Grade, IVORY ILOS | 1 | AEV |
| | All 125 VAC outlets shall be indicator lighted when power is applied to the outlet. | | |
| | Special order items, non-returnable, non-deletable. | | |
| | | | |
| 06-SO-14L4 | LOCATION: Telemetry Area, (See Drawing) | 1 | AEV |
| 06-SO-14O2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-1461 | < > 125 VAC Quad Outlet 2;15A, Lighted Hospital Grade, IVORY IATS | 1 | AEV |
| 00-00-1401 | All 125 VAC outlets shall be indicator lighted when power is applied to the outlet. | , | 76 |
| | Special order items, non-returnable, non-deletable. | | |
| | Special order items, non-returnable, non-deletable. | | |
| 06-SO-14L3 | > LOCATION: RF ALS, (See Drawing) | 1 | AEV |
| 06-SO-14D2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-13N3 | | 1 | AEV |
| 00-30-13N3 | > 125V W/ Dual USB (1-A & 1-C) & Power Light Outlet #3: 20A, Hosp | 1 | AEV |
| 00 00 4444 | Grade White IATS | 4 | 451/ |
| 06-SO-14L1 | > LOCATION: Action Area, standard location | 7 | AEV |
| 06-SO-14O2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-13N4 | > 125V W/ Dual USB (1-A & 1-C) & Power Light Outlet #4: 20A, Hosp | 1 | AEV |
| | Grade White IATS | | |
| 06-SO-14L1 | > LOCATION: Action Area, standard location | 1 | AEV |
| 06-SO-14O2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-1405 | 125 VAC Outlet, No 5: 15A, Hospital Grade, IVORY | 1 | AEV |
| 06-SO-14L1 | > LOCATION: Action Area, standard location | 1 | AEV |
| 06-SO-14O2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-1406 | 125 VAC Outlet, No 6: 15A, Hospital Grade, IVORY | 1 | AEV |
| 06-SO-14L7 | S LOCATION: M5 above Stair Chair pocket for charging new Ferno | 1 | AEV |
| 00-30-14L1 | Stair Chair | , | ALV |
| 06-SO-14O2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-1100 | **INTERIOR 12 Volt OUTLETS** | 1 | AEV |
| | | 1 | |
| 06-SO-1101 | 12V Outlet, No 1: Power Point Double Outlet- Wire thru Med Isolator | 1 | AEV |
| 06-SO-11L1 | > LOCATION: Action Area, standard location | 1 | AEV |
| 06-SO-14O2 | Outlet mounting ORIENTATION: Vertical | 1 | AEV |
| 06-SO-1910 | Power Source: Medical Isolator , Batt Sw Hot | 1 | AEV |
| 06-SO-116C | S <> DUAL USB, One Type A, One Type C+PD Round IATS EACH | 1 | AEV |
| | Includes waterproof cover. | | |
| | | | |
| | | | |
| 26-SO-11L1 | LOCATION: Action Area wall #2 | 1 | AEV |
| 06-SS-11A3 | > Siren: Carson, SA441-17F Mechanical, Mforce - 200watt, ILOS F | 1 | AEV |
| 06-SS-SA28 | > Siren Speakers:CPI: SA4327 with Black AEV laser cut cover, flush F | 1 | AEV |
| | series ILOS | | |
| 06-SS-SW01 | > Siren / OEM Horn Switch: In Cab Console | 1 | AEV |
| 06-SS-SW07 | Magnetic microphone clip for siren - install location TBD | 1 | AEV |
| | Install location to be declared | • | |
| | ?????????????? | | |
| | | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 18 |
|--------------------------|--|-------|---------|
| PART NO | S DESCRIPTION | QTY | ID |
| | part KITS-MAGIC (1) | | |
| 06 00 4242 | Air Harn Systems BUELL 54 | | AEV |
| 06-SS-1313 06-SS-1306 | Air Horn System: BUELL - F1 < Air Horns ACTIVATION Cole Hersee 12v switch &valve Lanyard | 1 | AEV |
| 00-33-1300 | Located at head liner between cab seats. | 1 | AEV |
| | Located at flead lifler between cab seats. | | |
| 06-SS-1305 | > Air Tank Mounted to Frame Rail | 1 | AEV |
| 06-SS-1310 | All Talik Mounted to Frame Kall | 1 | AEV |
| 06-SS-1310 | > Compressor: Buell #6540/5540 20% Oil less Intermittent Duty | 1 | AEV |
| 06-SS-1345 | Compressor Location: M6 Compartment | 1 | AEV |
| 06-SS-13F2 | Compressor Eccution: Mic Compartment Air Horn Location: Under Front Bumper, F-450 and F-550 2017 + | 1 | AEV |
| 00 00 1012 | For F-550 may require recess cut into ABS valance - Air Dam. | • | 71.20 |
| | , , | | |
| 06-SS-1321 | Left Air Horn: 10" Buel Strombos Horn, Chrome, No 1061 (493 Hz) | 1 | AEV |
| 06-SS-1332 | > Right Air Horn: 12" Strombos Horn, Chrome, No 1062 (396 Hz) | 1 | AEV |
| 06-SS-13M1 | Air horn exterior mounted system powder coated to gloss black | 2 | AEV |
| | Each | | |
| | Each air horn to be Dissasembled and taken to vendor for recoating; | | |
| | COAT-POWAIR (1) per air horn assembly one air horn typically 5 pieces | | |
| | Target color is Gloss black. | | |
| | | | |
| 07 00 0404 | CABINET SHOP - Modular | | AEV |
| 07-00-0181 | < Aluminum Cab Consoles contained in the Electrical System Section | | AEV |
| | Duplicate Notification location. Please pick the appropriate code at the Elect | rical | |
| | console section for the upcharge. | | |
| 06-RR-S500 | Aluminum Camada Drawina namusat | | AEV |
| 00-KK-3500 | Aluminum Console Drawing request AEV Engineering to develop drawing for console and send to Account manager | | AEV |
| | approval prior to release. | 101 | |
| | Console to include standard items. | | |
| | Removable top panel, inset | | |
| | Front location for Switch panel. | | |
| | all other items at special cost. | | |
| | dii otrici iteriis di special oost. | | |
| 07-00-0001 | < ALL DIMENSIONS ON ORDER WILL HAVE A VARIABLE OF + OR - 1/4" | 1 | AEV |
| | Unless specified as a minimum dimension. | | |
| | | | |
| | ***Aluminum - Expanded PVC Cabinet Configuration 172 Type 1 | | AEV |
| 07-00-0006 | TPR Matt : On Cabinet Floors, Drawers & Shelves, X-Series units | 1 | AEV |
| 07-00-0030 | < Aluminum Cabinet Backer-Sound Barrier | 1 | AEV |
| | # INSU-KSU on back side of aluminum cabinets | | |
| 07.00.14000 | | | A => / |
| 07-00-MB90 | Interior Color Packages | | AEV |
| 07-00-MC03 | Mica Color: Gloss White D354F-01 | 1 | AEV |
| 07-00-N002 | All Cabinet interiors Standard Pre-laminated > WHITE | 1 | AEV |
| 07-00-PC0N | > Polycarbonate Type/Color: Lexan - CLEAR Secure Latch | 7 | AEV |
| 07.04.7000 | Att. Seat EVS 1900 Exec with Per4Max 4-pt Belt with recline X-Series ILC | | AEV |
| 07-04-T302 | < > EVS 1900 Exec Seat Gunmetal ALL Per4max Black Belt recline X | 7 | AEV |
| | -Series ILOS | | |
| | Sewn Gunmetal with Gunmetal Insert Per4max Black belt | | |
| | recline feature | | |
| | Toolino toaturo | | |
| | | | |
| 07-SE-02X9 | > BASE: Swivel base for EVS Executive Seat Option X series ILOS | 1 | AEV |
| | | | |
| 11-SE-0505 | < Attendant Seat, Armrests, BOTH LEFT and RIGHT ARMS EVS | 1 | AEV |
| | Exec series x | | |
| | SEAT-EVSARMS | | |
| | | | |
| | | | |
| | | | |

| 08/18/2023 | | Job/Order No: 22OF 28438XA | | Page 19 |
|------------|---|---|------|---------|
| PART NO | S | DESCRIPTION | QTY | ID |
| 07-AC-4500 | < | AC CABINET: Evaporator, Location: Bulkhead X Series STD composite | 1 | AEV |
| | | Over Walkthru | | |
| | | Composite Construction | | |
| | | | | |
| 07-ZZ-ZZZZ | | <u> </u> | 1 | AEV |
| 07-CA-03XA | | > CURBSIDE UPPER: Over Squad Bench with Aluminum White Liners X | 1 | |
| 07-0A-03XA | | -IATS | , | 72 |
| 07 CH V407 | | | 4 | AEV/ |
| 07-CU-X107 | | Cabinet K1 & K2: (2) Openings with flush center divider | 1 | |
| 07-DR-M060 | • | > EZ -Reach Top- Hinged Single Overhead ILOS 40 LB EACH | | AEV |
| | | Color of Polycarbonate determined by overall color choice. | | |
| | | Top mounted Reel-TORQ30 | | |
| | | | | |
| 07-DR-M900 | | Secure Latch handle is NON-LOCKING | 2 | AEV |
| 07-DR-M905 | | No cable stop requested for doors | 2 | AEV |
| 07-DR-OR01 | | Hinge Orientation: TOP | 2 | AEV |
| 07-ZZ-ZZZZ | | | 1 | AEV |
| 07-CA-04A9 | | > Cabinet, (2) Glove Storage, over Rear Entry Doors | 1 | |
| 0. 0.1 0 | | Two glove dispenser over rear doors, (1) on each side of clock. | - | ' - ' |
| | | Two glove disperiser over real doors, (1) on each side of clock. | | |
| 07-DR-LX04 | | Door: Overlay He, 3/8" Lexan - 3-glove dispense thru | 4 | AEV |
| | | | | |
| 07-HW-SO11 | | > Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated | 1 | AEV |
| 07-ZZ-ZZZZ | | | 1 | AEV |
| 07-CA-04B0 | | CURBSIDE REAR STORAGE CABINET: NONE | 1 | · ·— · |
| 07-ZZ-ZZZZ | | | 1 | · ·— · |
| 07-LF-4500 | S | LF Cabinet, Behind Att Seat: Cabinet "H" X Series Aluminum/ | 1 | AEV |
| | | Composite | | |
| | | Facing Rearward | | |
| | | | | |
| 07-DR-WDX1 | | Door, Single Solid , Flush Fitted | 1 | AEV |
| 07-CA-2100 | | TRIM: U-shaped Door, J-trim opening | 1 | AEV |
| 07-DR-OR03 | | Hinge Orientation: LEFT | 1 | AEV |
| 07-HW-HIN1 | | Hinge: 1 1/2" Stainless Steel Piano Hinge | 1 | AEV |
| | | Round Pull Latch: Non-locking - Chrome Finish 10 lb rated each | 1 | AEV |
| 07-HW-SX11 | | | 1 | |
| 07-RF-4500 | S | | 1 | AEV |
| | | X-Series Design with 45° | | |
| | | But and death of the control of the | | |
| | | Reduce depth 8in to make room for secondary patient and cabinets at head |) of | |
| | | SB with 2 drawers and pull out sharp/trash | | |
| | | | | |
| | | Sliding Pocket Door Rear of ALS | | |
| | | | | |
| 07-CA-04AX | | > Cabinet, (3) Glove Storage, 45° Section of RF ALS cabinet, X-Series | 1 | AEV |
| 07-DR-LX0C | | Door: Overlay Hinged, 3/8" Lexan - 3-glove dispense thru X-SERIES | 1 | AEV |
| 07-DR-LZ10 | | Hinges: Stainless Spring Loaded | 2 | AEV |
| 07-HW-SX11 | | Round Pull Latch: Non-locking - Chrome Finish 10 lb rated each | 1 | AEV |
| 07-RF-0003 | | Interior Color: White Anti-Microbial Powder Coated | 1 | |
| 07-RF-I1X0 | | Cabinet I-1: Standard, Aluminum Composite Construction | 1 | |
| 07-DR-LXXE | | Door, Single Solid, Flush - Drug Locker | 1 | |
| 07-CA-2100 | | Door, Single Solid, Flush - Drug Locker TRIM: U-shaped Door, J-trim opening | 4 | AEV |
| | | | 1 | |
| 07-DR-OR02 | | Hinge Orientation: BOTTOM | 1 | AEV |
| 07-HW-HIN1 | | Hinge: 1 1/2" Stainless Steel Piano Hinge | 1 | AEV |
| 07-HW-REGR | • | Combination Lock: COMPX Regulator Right hand horizontal self | 1 | AEV |
| | | locking Each | | |
| | | COMPX Regulator self locking with keypad, | | |
| | | REG -S-R-3 Right hand horizontal with 1 3/16" length cylinder with self closing la | tch. | |
| | | Allows for the door to be slam latch style. | | |
| | | System provides one supervisor code, and one User code | | |
| | | | | |
| 07-DR-WS10 | • | Doors: Single Flush Fitted 6" Secure latch top of door | 1 | AEV |
| | | Secure latches installed at top of door. | | |
| | | | | |
| | | | | |
| | | | 1 | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 20 |
|----------------|--|-----|----------------|
| PART NO | S DESCRIPTION | QTY | ID |
| 07-CA-21A0 | TRIM: U-shaped Door, J-trim opening, DBL DRS | 1 | AEV |
| 07-HW-HIN1 | Hinge: 1 1/2" Stainless Steel Piano Hinge | 1 | AEV |
| 11-X0-0045 | Stowage rating label Secure Latch 6" Single Handle on Door 20 | 1 | AEV |
| 11-70-0040 | pounds applied | • | AL 1 |
| 07 77 7777 | | _ | Λ Γ \ / |
| 07-ZZ-ZZZZ | | 1 | AEV |
| 07-RF-I2X0 | Cabinet I-2: Standard, Aluminum Composite Construction | 1 | AEV |
| 07-DR-M052 | < > EZ- Reach Double doors ALS 1/2 LOS 40 LB | 1 | AEV |
| | Color of Polycarbonate determined by Lexan color choice. | | |
| | · | | |
| 07-DR-M900 | Secure Latch handle is NON-LOCKING | 1 | AEV |
| 07-DR-M905 | No cable stop requested for doors | 1 | AEV |
| | | - | |
| 07-DR-OR05 | Hinge Orientation: (1) RIGHT and (1) LEFT | 1 | AEV |
| 07-RA-IOA1 | Outside Access: Thru M-7 (RF) Compartment door. | 1 | AEV |
| 07-RF-0001 | Interior MICA Color: White cabinet liner | 1 | AEV |
| 07-TS-12X2 | Shelf Track: Small Alum. Unistrut, X-Series, RF ALS cabinet | 1 | AEV |
| 07-CA-06VD | (2) Shelves: Adjustable,Aluminum, White Anti-Microbial coated, STD | 1 | AEV |
| | | | AEV |
| 07-RF-I3X0 | S Cabinet I-3: X 50/50 With I-2, Aluminum Composite | 1 | |
| 07-DR-M054 | < > EZ- Reach Double-Doors ALS 1/2 LOS I-3 40 LB | 1 | AEV |
| | Color of Polycarbonate determined by Lexan color choice. | | |
| | · · · · · · · · · · · · · · · · · · · | | |
| 07-DR-M900 | Secure Latch handle is NON-LOCKING | 1 | AEV |
| 07-DR-M905 | No cable stop requested for doors | 1 | AEV |
| | | | |
| 07-DR-OR05 | Hinge Orientation: (1) RIGHT and (1) LEFT | 7 | AEV |
| 07-RA-IOA1 | Outside Access: Thru M-7 (RF) Compartment door. | 1 | AEV |
| 07-RF-0001 | Interior MICA Color: White cabinet liner | 1 | AEV |
| 07-ZZ-ZZZZ | ['] | 1 | AEV |
| 07-RR-0064 | S < Right Rear Cabinet: Cover over M-5 Compartment | 1 | AEV |
| 07-1111-0004 | 1 9 | | ALV |
| | Reduce 7 in to make room for secondary patient and cabinets at head of | 30 | |
| | with 2 drawers and pull out sharp/trash | | |
| | | | |
| | Reduced M5 | | |
| | | | |
| 07-SA-0000 | | 1 | AEV |
| | COLLAD DENICLE Alexanization Community Construction V Conica | 1 | |
| 07-SB-4500 | SQUAD BENCH: Aluminum Composite Construction X Series | | AEV |
| 07-SB-0001 | See Upholstery Section for Post and Wheel Cup info | 1 | AEV |
| 07-SB-1102 | < Bio-waste/Sharps No 1: Roll-out DRAWER (164) | 1 | AEV |
| | This Option is in lieu of Standard Bio-waste, normally located in the Action Area. | | |
| | This is the primary Bio-waste receptacle. | | |
| | This is the printary bio-waste receptable. | | |
| 07 1114/ 01 07 | Drawer Clides Pie Weste Heavy Date Flet Detechable 200 lb | _ | A =\/ |
| 07-HW-SL07 | < > Drawer Slides:Bio-Waste Heavy Duty Flat Detachable 300 lb | 7 | AEV |
| | capacity 16" ILOS | | |
| | 16" Long | | |
| | - | | |
| 07-HW-SO11 | > Round Pull Latch: Non-locking - Chrome Finish ILOS -10 lb rated | 1 | AEV |
| 07-SB-0999 | LOCATION: At head of Squad Bench, Roll out over step well | 1 | AEV |
| | | 1 | |
| 07-SB-1005 | | 7 | AEV |
| 07-SB-1008 | SHARPS CONTAINER: 2-Gallon Sharps-A-Gator (CONT-02) | 1 | AEV |
| 07-SB-1001 | Storage Under Lid - Configure to M-6 Compartment Size | 1 | AEV |
| 07-SB-LIDX | Squad Bench Lids: Split - 2-section | 1 | AEV |
| 07-SB-LH00 | Hinge, Squad Bench Lid(s): Butt Style Hinges | 1 | AEV |
| 07-SB-LH03 | Lid Checks: Gas shock, Dual Action | 2 | AEV |
| | | 2 | |
| 07-SB-LH08 | > Latch, Squad Bench Lid: Slam Action , KITS-SBL - Surface mount | 2 | AEV |
| | 80 LBS | | |
| 07-TR-SB01 | Edge Trim, Lids: Band w/ Laminate and J-Trim Protection | 1 | AEV |
| ZZ-ZZ-ZZZZ | | 1 | AEV |
| 08-MH-1404 | > Restraint Net, at head of S/B, NONE | 1 | AEV |
| | Noodiante Hot, at Hour of O/D, HOHE | 1 | |
| 08-ZZ-ZZZZ | | 1 | AEV |
| 07-TC-4500 | TOP CABINETS, - w/ 72" HR, Aluminum Composite Construction X STD | 1 | AEV |
| 07-TC-A450 | Cabinet A: 72" HR Aluminum Composite X std | 1 | AEV |
| 07-DR-M060 | < > EZ -Reach Top- Hinged Single Overhead ILOS 40 LB EACH | 1 | AEV |
| | Color of Polycarbonate determined by overall color choice. | - | |
| | Solor of Folysalbonate actornilled by Overall color choice. | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 21 |
|------------|---|----------|---------|
| PART NO | S DESCRIPTION | QTY | ID |
| | Top mounted Reel-TORQ30 | | |
| | · | | |
| 07-DR-M900 | Secure Latch handle is NON-LOCKING | 1 | AEV |
| | | 1 | |
| 07-DR-M905 | No cable stop requested for doors | 1 | AEV |
| 07-DR-OR01 | Hinge Orientation: TOP | 1 | AEV |
| 07-TS-12X0 | Shelf Track: Small Alum. Unistrut, X-Series | 1 | AEV |
| 07-CA-06VB | (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated | 1 | AEV |
| 07-ZZ-ZZZZ | | 1 | AEV |
| 07-TC-B450 | Cabinet B: Ergonomically angled toward the CPR seat (72"HR) X Std | 1 | AEV |
| | | | |
| 07-CB-DR75 | Doors; Cabinet B Secure Latch Restocking Sliding Window Top hinged | 1 | AEV |
| | x -30lb | | |
| 07-XA-3800 | > Divider System For Adjustable dividers w/ ABS slotted track - | 1 | AEV |
| | Each Cabinet | | |
| 07-XA-38A0 | Lexan Divider, Additional, requires option 07-XA-3800 | 1 | AEV |
| | | ' | |
| 07-TS-12X0 | Shelf Track: Small Alum. Unistrut, X-Series | 1 | AEV |
| 07-CA-06VA | S (2) Shelves: Adjustable, Aluminum, White Anti-Microbial coated | 1 | AEV |
| 07-ZZ-ZZZZ | I | 1 | AEV |
| 07-WC-0000 | I ' | 1 | AEV |
| 07-WC-4500 | > WALL CABINET: CPR Seat w/Telemetry, Aluminum Composite | 1 | AEV |
| 07-4400 | , | ' | ALV |
| | Construction X | | |
| 07-WC-AAX1 | Action Area: Standard | 1 | AEV |
| 07-CA-480Z | < > 1/2" Solid Surface A/A Tray W Tilt out below X-Series ILOS | 1 | AEV |
| | > In order to achieve an interior radius on the tray, some glue lines may be visible. | | |
| | in order to define the mineral radius on the tray, some give lines may be visible. | `` | |
| 07.04.4000 | | | 4 = 1 4 |
| 07-CA-4823 | Gibraltar (Solid Surface) Material COLOR: Midnight Melange | 1 | AEV |
| | 9091ML | | |
| 07-CA-4U08 | Solid Surface extension in front of O1 X series std | 1 | AEV |
| 07-CA-4U20 | Recess Opening below Action Area for Sharps container access | 1 | AEV |
| 07-0A-4020 | X-ILOS | • | 74 |
| 07.04.4404 | | | 4 = 1 4 |
| 07-CA-4U21 | Bio-waste No 1: (1) Tilt-out Door (Wall cabinet) X ILOS | 1 | AEV |
| 07-CA-2100 | TRIM: U-shaped Door, J-trim opening | 1 | AEV |
| 07-DR-M900 | S Secure Latch handle is NON-LOCKING | 1 | AEV |
| 07-DR-OR02 | Hinge Orientation: BOTTOM | 1 | AEV |
| 07-DR-WE01 | Location; Forward of the CPR seat | 1 | AEV |
| | • | <u>'</u> | |
| 07-SB-1011 | > SHARPS/Bio Waste CONT. 5-Quart Kendall # 85131 | 1 | AEV |
| | RED(CONT-03) | | |
| 07-WC-AABH | < Action Area Board: (GLOSS BLACK Formica ILOS) See Station No | 1 | AEV |
| | 6 for content | | |
| | With Chrome Trim | | |
| | | | |
| | MICA-W100 | | |
| | Vertical back wall to be Gloss Black Formica In Lieu of black grip material. | | |
| | | | |
| | | | |
| 07-ZZ-ZZZZ | | 1 | AEV |
| 07-ZZ-ZZZZ | | 1 | AEV |
| | I . | • | |
| 07-WC-O10X | Cabinet O1: Standard, Aluminum Composite Construction | 1 | AEV |
| 07-DR-M064 | < > EZ -Reach Side- Hinged Single Window ILOS-40 LB | 1 | AEV |
| | Color of Polycarbonate determined by overall color choice. | | |
| | , , , , , , , , , , , , , , , , , , , | | |
| 07-DR-LZ10 | Hinges: Stainless Spring Loaded | 2 | AEV |
| | | | |
| 07-DR-M900 | Secure Latch handle is NON-LOCKING | 1 | AEV |
| 07-DR-M905 | No cable stop requested for doors | 1 | AEV |
| 07-DR-OR04 | Hinge Orientation: RIGHT | 1 | AEV |
| 07-TS-12X0 | Shelf Track: Small Alum. Unistrut, X-Series | 1 | AEV |
| 07-CA-06VB | (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated | 1 | AEV |
| | | 1 | |
| 07-WC-C003 | Cabinet C: DELETE | 7 | AEV |
| 07-WC-D64X | Cabinet D: Ergonomically Angled Over Telemetry, Alum | 1 | AEV |
| | Composite Construction | | |
| 07-CB-DR7D | < > Doors; Cabinet D Secure Latch Restocking Sliding Window Top | 1 | AEV |
| | hinge x -30lb | • | |
| | | | |
| | (1) WIND-CFTG | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 22 |
|-------------|--|-----|------------|
| PART NO | S DESCRIPTION | QTY | ID |
| 07-TS-12X0 | Shelf Track: Small Alum. Unistrut, X-Series | 1 | AEV |
| 07-CA-06VB | (1) Shelf: Adjustable, Aluminum, White Anti-Microbial coated | 1 | AEV |
| 07-ZZ-ZZZZ | l | 1 | AEV |
| 07-WC-E003 | Cabinet E: DELETE | 1 | AEV |
| | Cabinet E. DELETE | | |
| 07-ZZ-ZZZZ | I | 7 | AEV |
| 07-WC-F64X | Cabinet F: Standard, Aluminum Composite Construction | 1 | AEV |
| 07-CB-DR7F | < > Doors; Cabinet F Secure Latch Restocking Sliding Window | 1 | AEV |
| | Bottom hinged x | | |
| | Bottom hinged, Damper assist. | | |
| | (1) WIND-CFBD custom sized | | |
| | (1) WIND-OI DD Custom sized | | |
| 44.1/0.0040 | | | 4 = 1 (|
| 11-X0-0016 | Stowage rating label Secure Latch Restocking Sliding Window | 7 | AEV |
| | 30 pounds applied | | |
| 07-ZZ-ZZZZ | | 1 | AEV |
| 07-WC-SS02 | Side Seat: 24" - Single Position - Under Lid Storage w/Latch | 1 | AEV |
| 07-WC-BA00 | Hinge, CPR Seat Lid(s): Butt Style Hinges | 1 | AEV |
| 07-WC-BR01 | Back Rest: Fixed to Back Wall of CPR Seat w/clips | 4 | AEV |
| | | | |
| 07-WC-ST52 | > CPR Seat, Lid check Gas shock dual action installed | 1 | AEV |
| 07-WC-TAX1 | Telemetry Area: with armrest pad | 1 | AEV |
| 07-CA-49X0 | < > 1/2" Solid Surface Telemetry Area Tray: X-Series STD | 1 | AEV |
| | > In order to achieve an interior radius on the tray, some glue lines may be visible. | << | |
| | <i>y,</i> 5 | | |
| 07-CA-4T23 | Gibraltar (Solid Surface) Material COLOR: Midnight Melange | 1 | AEV |
| 08-SE-1702 | P4 - 4-Point PER4MAX Restraint System - W/CPR | 1 | AEV |
| | | | |
| 08-SE-1847 | < > (2)Per4max above Squad Bench, (1) Per4Max above CPR Side | 1 | AEV |
| | Seat Black Belts | | |
| | Belt retractors can mount above the seat level, | | |
| | | | |
| | | | |
| 08-SE-SB70 | > S/B: (3) Sec patient restraints - 9" Sleeves Face of Bench | 1 | AEV |
| 08-SE-SB76 | S/B: (3) Sec patient restraints - 5" Sleeves By Hinge | 1 | AEV |
| 08-SF-0040 | | 3 | |
| 00-3F-0040 | | 3 | ALV |
| | Headrest X-std | | |
| 00-20-0072 | Per4Max Four-Point Seatbelts: Accept and Install Full Feature | 1 | AEV |
| 07-ZZ-ZZZZ | | 1 | AEV |
| | CABINET SET - CELL 4 - MOD | | AEV |
| 08-00-00CX | > Sub Floor, 3/4" Composite, STD | 1 | AEV |
| 07-RR-2302 | < Customer Radio: Space for Customer installed Radio Heads Alum Panel, | 1 | AEV |
| 0 2002 | Black | - | |
| | an Aluminum panel to bolt into the modular console system | | |
| | an Administrative politimo the modular console system | | |
| 07.00.0070 | | | 4 = 1 (|
| 07-SB-0050 | Custom Cabinet/Cabinets: At Head of Squad Bench Area | 1 | AEV |
| 07-CA-490S | < > 1/2" Solid Surface Squad Head Storage Top Tray: | 1 | AEV |
| | The tray shall have a lip. The tray lip shall come up to the front and overlay the fac | e. | |
| | > In order to achieve an interior radius on the tray, some glue lines may be visible. | | |
| | ,, 3 | | |
| 07-CA-4T23 | Gibraltar (Solid Surface) Material COLOR: Midnight Melange | 1 | AEV |
| | | | |
| 07-DW-0010 | Drawers: (2) Mica-wood body, Mica inside and out | 7 | AEV |
| 07-DR-WSD1 | Drawer Front: Flush Fitted with 12" secure latch at top | 2 | AEV |
| | | | |
| | | | |
| 07-CA-2100 | TRIM: U-shaped Door, J-trim opening | 2 | AEV |
| 11-X0-0048 | Stowage rating label Secure Latch 12" Single Handle on Door 40 | 2 | AEV |
| 2.2.0 00-70 | pounds applied | _ | |
| 07-HW-SL01 | < > Drawer Slides: Full Extension, Detachable 130 LB capacity STD 18" | 2 | AEV |
| UI-HW-SLUT | • | _ | AEV |
| | long | | |
| | Slides installed Vertical at Sides ONLY. 18" Long | | |
| | | | |
| 08-00-FL3A | Flooring: Loncoin II Flecks- #150, Onyx (Black) | 1 | AEV |
| 08-00-FL0D | < > Flooring HALO Edge, 3" Recessed 3/4" w/ RGB All color-LED Lighted | 1 | AEV |
| | roll-up | _ | |
| | . on up | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 23 |
|--------------|--|--------|------------|
| PART NO S | DESCRIPTION | QTY | ID |
| | Recessed roll up- requires 3/4" cabinet main face and squad main face. Install | | |
| | trim with All-color strip in channels with light attached. Lights on sides of floor re | oll up | |
| | only. | | |
| | >>>> Requires additional choice of option 07-00-2005 <<<< | | |
| | Lights to activate when rear doors and curbside doors open | | |
| | > engineering to design light kit after cabinet design <<<< EE work required. | | |
| | | | |
| 05-IL-01Y0 | Separate controller for HALO perimeter Edge color | 1 | AEV |
| 08-AS-0001 | Rear Threshold, Stainless, 6" Wide x Full Width at rear doors | 1 | AEV |
| | Install safety yellow with diagonal stripes nonskid tape over threshold. | | |
| | | | |
| 08-AS-0006 | C/S Stepwell Threshold, Polished Diamond Plate | 1 | AEV |
| 08-AS-000H | C/S Threshold Extension, 3" Wide Stainless Steel w Safety Grip | 1 | AEV |
| | Tape IATS | | |
| | Butt against std Curbside threshold, Secure on top of flooring. | | |
| | Width of curbside entry threshold only, | | |
| | | | |
| | | | |
| 08-ZZ-ZZZZ | | 1 | AEV |
| 08-CR-09PP | < Cot Mount: Stryker, No 6390, Power Load, Prep ONLY >>NON COMPLIANT | 1 | AEV |
| | << | | |
| | This will have everything need for Customer/Dealer to install the Stryker Power Lo | oad | |
| | system at a later date. | | |
| | Constant hot and ground service power provided, | | |
| | Prep will include, installation of Floor Plate Kit | | |
| | THIS DOES NOT INCLUDE ANY COT MOUNT | | |
| | >>>>> EXCEPTION TO 3.11.6 >> THIS is an incomplete installation, an exception | n is | |
| | required, NON COMPLIANT installation. | | |
| | | | |
| 08-CR-0420 | > Non-Compliant to SAE J3027, J3102 3.11.6 Patient Cot Mount Notice | 1 | AEV |
| 08-CR-0421 | > Non-Compliant to SAE J3027, AMD 004 CAAS GV 1.0 C.11.6 | 1 | AEV |
| 08-CR-09PN | mass casualty kit not requested | 1 | AEV |
| 08-CR-1001 | < 12v power for cot mount provided up through floor | 1 | AEV |
| | 12volt power for power load to be brought through floor, with Heat shrink connect | ors | |
| | installed | | |
| | | | |
| 08-CS-00PL | < Cot Position No 1: PRIMARY CENTER POSITION, | 1 | AEV |
| | Maintain 12" between Cot and S/B. | | |
| | | | |
| 08-CS-2000 | < > Primary Cot position under floor reinforcement | 1 | AEV |
| | Install 8 inch wide by 5 long 1/2" aluminum reinforcement at primary cot position. | | |
| | (Primary cot position only - REV Std) | | |
| | **If custom location is desired, must be specified below. | | |
| | | | |
| 08-CS-3009 | Cot mount set up for: Stryker Power-Pro 6506 | 1 | AEV |
| 08-CS-3009 | Cot mount set up for: Stryker Power-Pro 6506 | 1 | AEV |
| 08-CS-0001 | COT MOUNT HARDWARE: (Full Size Mod) | 1 | AEV |
| 08-OS-04SX | OXYGEN / AIR / VACUUM System: X-Series | 1 | AEV |
| 08-OS-0401 | > Oxygen Outlet No 1: Amico Console - Ohmeda/Ohio Diamond Style | 1 | AEV |
| 08-OS-040A | LOCATION: Action Area | 1 | AEV |
| 08-OS-0402 | Oxygen Outlet No 2: Amico Console - Ohmeda/Ohio Diamond Style | 1 | AEV |
| 08-OS-040A | LOCATION: Action Area | 1 | AEV |
| 08-OS-0403 | Oxygen Outlet No 3: Amico Console - Ohmeda/Ohio Diamond Style | 1 | AEV |
| 08-OS-040D | > LOCATION: Curbside Wall, over the head of the S/B | 1 | AEV |
| 08-OS-090X | Port Cyl Rack No 1: Zico QR-D-2 - D or Jumbo D - No Strap Req | 1 | AEV |
| | Through bolt the rack to metal. | | |
| | | | |
| 08-OS-09L1 S | > Rack Location : Recesesed Aisle side of RF ALS cabinet | 1 | AEV |
| 08-OS-0505 | < > Rack No 1: Zico OTS M/H Cylinder LIFT Switch recessed on door, | 1 | AEV |
| | Motor Left, ILOS | | |
| | Lift with QR-MV universal Bracket. QR-OTSL-U | | |
| | | | |

| 08/18/2023 | | | Job/Order No: 22OF 28438XA | | Page 24 |
|-------------|----|-------|--|--------------|---------|
| PART NO | S | | DESCRIPTION | QTY | ID |
| | | | Make sure Oxygen Hose is long enough for lift to be fully deployed. | | |
| | | | ,,,,,,,, - | | |
| | | | | | |
| 00 00 00 10 | | | | | 4 = 1 (|
| 02-B0-CC42 | | < > | | 1 | AEV |
| | | | MTB to increase compartment floor thickness to .25 inch smooth aluminum. | | |
| | | | | | |
| 08-OS-0002 | | < | Rack Set up for: "H" | 1 | AEV |
| 00 00 0002 | | • | steel H tank is 8 1/2" diameter x 55" tall 244 cu feet | • | / L_ V |
| | | | | | |
| | | | Aluminum H (M250) tank 9" diameter x 52" tall | | |
| | | | | | |
| 08-OS-0752 | | < | Activation, Zico O2 Lift, Door Mounted | 1 | AEV |
| | | | Mounted on compartment inner door panel | | |
| | | | | | |
| 00 00 0040 | | | Owner Hass Betweeter Highest Tool Belones | 4 | 451 |
| 08-OS-0810 | | > | 1, 3 | 1 | AEV |
| 08-OS-11G1 | | < | Cylinder Type: OXYGEN - Green Colored Hose | 1 | AEV |
| | | | Regulator connection Nut: 9/16" RH thread. | | |
| | | | • | | |
| 08-OS-1323 | | | Rack Location: M-1(LF), Wall #2 | 1 | AEV |
| 08-OS-1902 | | | | 1 | AEV |
| | | | Regulator Wrench: Cast aluminum, OXYGEN w/ cable lanyard | _ | |
| 08-OS-1490 | | < | Oxygen system Low and High pressure alarms LX-1 installed | 1 | AEV |
| | | | (1) SWIT-APF40 | | |
| | | | (1) SWIT-APF75 | | |
| | | | installed on the oxygen system after the regulator with feedback sent to the LX | K_1 | |
| | | | | N - 1 | |
| | | | electrical system. | | |
| | | | Low pressure alarm at 40 PSI | | |
| | | | High pressure alarm at 75 PSI | | |
| | | | | | |
| 08-OS-35ST | | | Vacuum System: SSCOR regulator/gauge panel in A/A | 1 | AEV |
| 08-OS-3501 | | > | | 1 | AEV |
| | | | | 1 | |
| 08-OS-3502 | | | VAC Plumbing: Direct from panel to canister - NO Outlet | 1 | AEV |
| 08-OS-3503 | | | Vacuum Pump: 49 State | 1 | AEV |
| 08-OS-35L8 | | > | Location: M-1a Compartment | 1 | AEV |
| 08-ZZ-ZZZZ | | | The state of the s | 1 | AEV |
| 00 22 2222 | | | TRIM / DOOR ASSEMBLY - CELL 5 | · | AEV |
| 00 00 0000 | | | | | |
| 09-00-002S | | | Interior window and aluminum trim with standard satin finish- std | 1 | AEV |
| 09-FE-05SS | | < > | Fire Extinguisher, 5 pound, Kidde ABC Installed, ILOS | 1 | AEV |
| | | | Part No: EXTI-01 | | |
| | | | Must be mounted Vertical to meet SAE Safety testing. | | |
| | | | | | |
| | | | Can not lay down in the vehicle. | | |
| | _ | | | | |
| 09-FE-04L2 | S | < | Fire Extinguisher installed at Special location, | 1 | AEV |
| | | | Location Determined at time of Dealer Inspection | | |
| | | | • | | |
| 09-FE-0621 | | < | Fire Extinguisher mounting bracket - Use std fork with band | 1 | AEV |
| 03-1 L-0021 | | | | , | ALV |
| | | | included Installed | | |
| | | | Compliant mount when mounted vertically ONLY. do not lay down this bracket. | | |
| | | | | | |
| 09-FE-05ST | | | Fire Extinguisher, 5 pound, Installed, IATS | 1 | AEV |
| 09-FE-04L1 | XS | < > | | 1 | AEV |
| 00 / 2 042/ | Λ0 | • • • | Location Determined at time of Dealer Inspection | • | / L_ V |
| | | | Location Determined at time of Dealer Inspection | | |
| | | | | | |
| 09-FE-0621 | | < | Fire Extinguisher mounting bracket - Use std fork with band | 1 | AEV |
| | | | included Installed | | |
| | | | Compliant mount when mounted vertically ONLY. do not lay down this bracket. | | |
| | | | James and the state of the stat | | |
| 00 00 0004 | | | | 4 | ۸ ۵ ۷ |
| 09-00-0001 | | | | 1 | AEV |
| 09-00-000Z | | | ******Door Department X Series > New | 1 | AEV |
| 02-BT-C85V | S | | Handles, Ext: Tri-mark 1875, Free Float, Black finish X-Series | 1 | AEV |
| 02-BT-C85A | | > | | 1 | AEV |
| | | < > | | 1 | |
| 02-BT-C902 | | · > | | 7 | AEV |
| | | | Illumination | | |
| | | | | | |
| | | | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 25 |
|--------------------------|---|-------|-------------------|
| PART NO | S DESCRIPTION >> AEV door department, Drill hole in top of recess dish handle to accept light be | QTY | ID |
| | Install light, One for every compartment and Entry door | illei | |
| | caution, long lead time part>> | | |
| | Lights must de-activate when shifted out of park. | | |
| | -g | | |
| 09-B1-ED0X | Entry Door Panels, Windows and Hardware, X-Series Units | 1 | AEV |
| 08-MH-0010 | Interior Grab Handle Color: Gray Antimicrobial | 1 | AEV |
| 08-MH-0319 | Grab Handle, CS Entry: (1) 3-pt "L" Shaped 90, Gray Antimicrobial | 1 | AEV |
| | ILOS | | |
| | Install CS door handle after cabinet installation. Close the doors and check for pi | nch | |
| | points or cabinet interference. | | |
| | | | |
| 08-MH-03E9 | Grab Handles, Rear Access: (2) 3-pt "L" Shaped 90, Gray | 1 | AEV |
| 00 11111 0020 | Antimicrobial | | 7120 |
| | | | |
| | | | |
| | | | |
| 09-AS-2300 | Door Panels: Mica Upper / Upholstery / Stainless Steel Lower | 1 | AEV |
| | The mica and stainless are laminated to smooth aluminum. | | |
| 00 40 2520 | Curbaida Lawer Daar Banali Stainlean | 4 | A = \/ |
| 09-AS-2520 09-E1-23B1 | Curbside Lower Door Panel: Stainless < > Multi-Color Printed LOGO: (3) Entry Doors, Customer Logo, requires | 1 | AEV AEV |
| 09-L1-23D1 | clear image | , | ALV |
| | Printed Multi-color logo onto panel, Back side lighted with LED lighting. | | |
| | ENG > to VENDOR | | |
| | PANL-DLW6X702 (3) 6x7 door logo w LED KINEQ | | |
| | | | |
| 09-WI-02BX | < > "AUTO SHADE" Windows: Upper R/A Doors, Fixed Glass, X-STD | 1 | AEV |
| | 16.375" w x 19.3"H | | |
| | WIND-H0161 (2) | | |
| | WIND-SMART film (2) | | |
| 09-WI-06BX | < > "AUTO SHADE" Window: Upper C/S Access, Fixed Glass, X-Series STD | 1 | AEV |
| OS WI OOBX | WIND-H0161 1 kit | | / \L V |
| | WIND-SMART 1 | | |
| | | | |
| 09-WI-09BX | > Inverter, "Auto Shade" Windows : Part of X series windows | 1 | AEV |
| 09-IN-3STX | Insulation: All Module Doors, 2" Black Foam, X-Series units | 1 | AEV |
| | #INSU-ARM2 | | |
| OO IN OCTV | Landstine All Madula Danie Diado Cound Diadfine V Conica unita | 1 | Λ Γ \ / |
| 09-IN-3STY | Insulation: All Module Doors, Black Sound Proofing, X-Series units #INSU-KSU | 1 | AEV |
| | #11/30-1/30 | | |
| 09-MH-2530 | < > Grab Rail, (1), 18" Gray Antimicrobial Rear Entry Assist std. | 1 | AEV |
| 00 1/11 2000 | Located: Module interior at the rear entry, mounted to the M5 compartment filler. | | / \L_ V |
| | is to be through bolted into M5. | | |
| | | | |
| 09-MH-2703 | > Grab Rail, C/S wall, curve out over C/S Entry, Gray Antimicrobial | 1 | |
| 09-DR-WT07 | > Walk through Door: Sliding, Into Pocket on Bulkhead ILOS | 1 | AEV |
| 09-FM-10X3 | Dri-Dek Compt Floors and shelves, Black, STD X-Series | 1 | AEV |
| 09-FM-11X0 | > Dri-Dek EDGES: Black, Beveled frontal edges | 1 | AEV |
| 07-ZZ-ZZZZ | ELECTRICAL Point to Point - CELL 6 | 1 | AEV AEV |
| 10-00-0110 | Space for recess full body comm. radio head at action area | 1 | AEV AEV |
| 70-00-0110 | Full body radio to be installed after factory delivery | | 7L V |
| | Depth required for full body radio | | |
| | | | |
| 10-EB-13X2 | > Cabinet Light(s): "DAY BRIGHT" LED White Lights, X-Series Units | 1 | AEV |
| 05-IL-13S1 | Cab Interior Lights Switching: Thru MultiPlex System | 1 | AEV |
| | | | |
| | | | |

| 08/18/2023 | Job/Order No: 22OF 28438XA | | Page 26 |
|-------------|---|-----|---------|
| PART NO S | | QTY | ID |
| 10-EB-13Y0 | Daybright location 1 | 1 | AEV |
| 10-EB-13YB | Daybright Light Location Cabinet B | 1 | AEV |
| 10-EB-13Y1 | Daybright location 2 | 1 | AEV |
| 10-EB-13YD | Daybright Light Location Cabinet D | 1 | AEV |
| 10-EB-13Y2 | Daybright location 3 | 1 | AEV |
| 10-EB-13YO | Daybright Light Location Cabinet O1 | 1 | AEV |
| 10-EB-13Y3 | Daybright location 4 | 1 | AEV |
| | | - | |
| 10-EB-13YF | Daybright Light Location Cabinet F | 1 | AEV |
| 10-EB-13Y4 | Daybright location 5 | 1 | AEV |
| 10-EB-13YI | Daybright Light Location Cabinet I-1 | 1 | AEV |
| 10-EB-13Y5 | Daybright location 6 | 1 | AEV |
| 10-EB-13YM | Daybright Light Location Cabinet I-2 | 1 | AEV |
| 10-EB-13Y6 | Daybright location 7 | 1 | AEV |
| 10-EB-13YN | Daybright Light Location Cabinet I-3 | 1 | AEV |
| 10-EB-13Y7 | Daybright location 8 | 1 | AEV |
| 10-EB-13YK | Daybright Light Location Cabinet K | 1 | AEV |
| 10-EB-13Y8 | Daybright Light Education Cabinet K | 1 | AEV |
| | | | |
| 10-EB-13YL | Daybright Light Location Cabinet K2 | 1 | AEV |
| 10-EB-13Y9 | Daybright location 10 | 1 | AEV |
| 10-EB-13YA | Daybright Light Location Cabinet A | 1 | |
| 10-IL-02SL | Action Area Light: 12V, Kinequip #621836W, 18", LED Rail Light | 1 | AEV |
| 10-IL-02L7 | Light Location: Action Area | 1 | AEV |
| | UPHOLSTERY - CELL 7 | | AEV |
| 11-00-UB95 | < Upholstery Color: Black (Black) UPHO-6905 | 1 | |
| 11 00 0200 | UPHO-6905 | | 7127 |
| | 01110-0000 | | |
| 11-00-UC11 | Contay Travel Unbalatory Colory Color Voy to Boot of Twick | 4 | 451/ |
| | Center Trough Upholstery Color: Color Key to Rest of Truck | 1 | |
| 11-00-UT0X | Uph Joint Type: "PREMIUM " Upgrade-X series Standard | 1 | |
| 11-SB-0005 | Squad Bench seat cushion cut-outs: None | 1 | AEV |
| 11-SB-0003 | Post And Wheel Cups: NONE | 1 | AEV |
| 11-SE-CSPD | Head Protection: Pad over CS Entry Door | 1 | AEV |
| 11-SE-REPD | Head Protection: 2" Pad over Rear Access Doors, Full Width | 1 | AEV |
| 11-MC-1630 | < > Clock, Digital 12VDC, BRG SA625 2.5" tall Red Number 24 HR format | 1 | AEV |
| | .Clock set to RED number, 24 Hour format, 12volt constant power | | |
| | Color can be reset to 7 different colors, changed to 12 hour format, 6 digit read | hut | |
| | Hours, minutes, seconds | Jut | |
| | nours, minutes, seconds | | |
| 44 140 4000 | | _ | 4=14 |
| 11-MC-1800 | Location: Over Rear Doors | 1 | |
| | PAINT - STRIPES - DECALS | | AEV |
| 12-PT-UNCT | Undercoating : Per QVM Guidelines, STD | 1 | AEV |
| 12-00-0150 | < Exterior Aluminum Bolt-on parts Black Out package Powder coated | 1 | AEV |
| | The following items are to be assembled by AEV production and sent to 3rd party | for | |
| | Gloss Black Powder coating; | | |
| | A front OEM bumper only (not a repalcement bumper, that is seperate code) | | |
| | front of module body diamond plate stone guards | | |
| | corner caps 4 pieces | | |
| | | | |
| | skirt rail kit 4 pieces | | |
| | rear bumper assembly including flip step | | |
| | Running boads (if purchased seperatly), | | |
| | front and rear plates for running boards 4pcs | | |
| | rear bumper pontoon covers aluminum diamond plate | 1 | |
| | rear kick plate with integrated license plate holder | | |
| | fuel fill bezel from body side | | |
| | Urea cast assembly from body side | | |
| | Fuel and def overfill lower plates (if purchased seperately) | | |
| | Curbside entry lower threshold, bottom one only | | |
| | | | |
| | Rear entry threshold one piece | -4 | |
| | >> Black powder coating is an appearance package and is not warranted again | | |
| | stone chipping where road debris may come into contact. The rear flip step is | not | |
| | coated due to the constant contact with the patient cot. | | |
| | | 1 | |
| | | | |
| | | | |

| 08/18/2023 | | | Job/Order No: 22OF 28438XA | | Page 27 |
|--------------------------|---|-----|--|-----|---------|
| PART NO | S | | DESCRIPTION | QTY | ID |
| 12-00-015W | | | Black Powder-coat 1 set of stainless steel wheel simulators IATS | 1 | AEV |
| 12-00-0170 | S | < | Side entry door interior trim pieces at floor level- Powder Coat | 1 | AEV |
| | | | please specify BLACK or Yellow | | |
| | | | | | |
| 12-00-0172 | S | < | Rear module flip step, Powder Coat | 1 | AEV |
| 12 00 0112 | | | Send to Paint shop for Coating | _ | 7 |
| | | | >> Item may chip due to constant contact with COT, | | |
| | | | reminay only due to constant contact with 601, | | |
| 12-00-0200 | _ | | I Pourder Coot PLACK | | 4 E \ / |
| | S | | Powder Coat BLACK | 1 | AEV |
| 12-00-0174 | 5 | < | | 7 | AEV |
| | | | Compartment sills outward only, lower body edge below the compartment f | | |
| | | | to be speedliner coated > Gray <, does not include upcharge to coat ea | ıch | |
| | | | compartment . | | |
| | | | | | |
| 12-00-0179 | | < > | Optional Running boards are Sand Blasted and Speedliner coated | 1 | AEV |
| | | | Send running boards for Sand Blasting | | |
| | | | Then process to Paint for Speedliner coating, | | |
| | | | Confirm Color Black ??????? | | |
| | | | | | |
| 12-00-0200 | S | | Powder Coat color BLACK | 1 | AEV |
| 12-DC-0001 | | | Reflective Tape: White Reflective On Painted edges of Exterior Door Frame | 1 | AEV |
| 12-DC-GA20 | | _ \ | Compartment Finish: Other than Diamond Plate | | AEV |
| 12-DC-GAZU | | ` ' | | ' | ALV |
| | | | Paint Shop to Refer to Body Section of Shop Order for Details. | | |
| 12-PT-0100 | _ | | Drimany (Over All) Colors Cress | | AEV |
| 12-21-0100 | 3 | < | | 1 | AEV |
| | | | AEV Paint Graphics Estimate # 02980 Total: | | |
| | | | 8/3/2023 8:12:45 AM Carroll County Randall Pennington | | |
| | | | AEV | | |
| | | | Details: | | |
| | | | Align Lights to Chevrons | | |
| | | | Paint Type I Cab | | |
| | | | Match Grey | | |
| | | | Paint Code 80052S and 650 | | |
| | | | Install 4" Inkjet Tape Belt. | | |
| | | | Install Custom QRS | | |
| | | | Tape: | | |
| | | | Side Chevrons | | |
| | | | Side SOL | | |
| | | | Lettering | | |
| | | | Window Perf on 3 windows | | |
| | | | Vinyl: | | |
| | | | Two Color Reflective Chevron on Entire Rear | | |
| | | | TWO COIOT Reflective Chevron on Entire Real | | |
| 12-DC-0002 | | | Flip Step Reflective/Prismatic Tape: Red/White/R/W/R/W/R | 1 | AEV |
| 12-DC-0002 12-PT-0112 | | | Tape Stripe: NONE (KKK-F Deviation) | 1 | AEV |
| | | | | | |
| 11-YZ-0962 | | | Non-Compliant toKKK-F 3.16.2 ;Exterior Safety stripe to be Orange | 1 | AEV |
| 12-PT-0600 | | | Paint Belt: NONE | 1 | AEV |
| 12-PT-1000 | | | Pin Stripe: NONE | 1 | AEV |
| 12-ZZ-ZZZZ | | | | 1 | AEV |
| 12-PT-RF01 | | > | The state of the s | 1 | AEV |
| 12-PT-1000 | | | Pin Stripe: NONE | 1 | AEV |
| 12-ZZ-ZZZZ | | | | 1 | AEV |
| 12-PT-2000 | | | Lettering: NONE | 1 | AEV |
| 12-ZZ-ZZZZ | | | | 1 | AEV |
| 12-PT-DRIP | | < | Drip Rails: Bright Aluminum, De-burred and rounded corners | 1 | AEV |
| _ : | | | Include a drip rail over the C/S Entry Door. | - | |
| | | | | | |
| 12-ZZ-ZZZZ | | | | 1 | AEV |
| | | | DETAIL - SHIP LOOSE ITEMS | | AEV |
| 12-PT-DRIZ | | < | Drip Rails: Detail-Refer to Paint Section for Drip Rail Information | 1 | |
| 12 1 1 01(12 | | | Include a drip rail over the C/S Entry Door. | 1 | / (L V |
| | | | morado a drip fair ovor the oro Littly boot. | | |
| | | | | | |

| 08/18/2023 | Job/Order No: 220F 28438XA | 0=1 | Page 28 |
|------------|---|------|---------|
| PART NO S | | QTY | |
| 13-00-0200 | *Check front of W/O under chassis section for Add' items* | | 1 AEV |
| 13-10-XM00 | Owner's Manual USB Flash Drive ship loose | | 1 AEV |
| 13-10-XMA0 | Printed Owner's Manual Not Required | | 1 AEV |
| 13-00-0001 | | _ | 1 AEV |
| 13-GL-0000 | Glove Holder, Ship Loose: NONE | 1 | 1 AEV |
| 13-KK-KDEC | > Decals: KKK / DOT Pkg, Blue/White reflective - Ship Loose | | 1 AEV |
| 13-RF-STAS | Decals: 32" Star of Life - Ship Loose | , | 1 AEV |
| 13-KK-NSSB | Decals: NO SMOKING & SEATBELT, installed, cab & pt. area. | 1 | 1 AEV |
| 13-KL-0013 | AEV Logos: SHIP LOOSE, Not Installed | , | 1 AEV |
| 13-MH-05ST | > Fire Extinguisher, 5 pound, shipped loose, Std | | 1 AEV |
| 11-YZ-0932 | Exception to 3.15.2 Required Two fire extinguishers installed by FSAM | , | 1 AEV |
| | Fire extinguishers were not installed with one in the driver's cab, one in the pat | ient | |
| | compartment at the time of departure from the final stage Ambulance Manufacture | | |
| | The customer/FSAM has shipped them loose for the dealer to complete the fi | | |
| | install. | | |
| | | | |
| 11-ZZ-0932 | Exception to C.16.1 1 Required Two fire extinguishers installed by FSAM | | 1 AEV |
| 11 22 0002 | Fire extinguishers were not installed iwth one in the driver's cab, one in the pat | | . , , , |
| | compartment at the time of departure from the final stage Ambulance Manufacture | | |
| | comparations at the time of departure from the final stage / imbalance manufacture | | |
| 13-MH-10A0 | > Reflector Pkg: Body - 2ea, Side Fr Amber, Side Rear Red, Rear Red | | 1 AEV |
| 13-SB-0003 | Post And Wheel Cups: NONE | | 1 AEV |
| 13-SP-TIRE | Spare Tire: Refer To Chassis Section to See if it gets one. | | 1 AEV |
| 34-XX-5000 | | | 1 AEV |
| 34-77-3000 | | | I AEV |
| | The purchaser agrees to defend, indemnify and hold REV harmless from any clair | | |
| | costs (including actual attorneys' fees), damages and liabilities caused in whole d | | |
| | part by any alteration or modification of, or changes or additions to the Purchas | ea | |
| | Products OR use of product for purposes it was not designed or intended for. | | |
| | | | |
| | == 172 x 96 T-1 LWB Ford X Base Price - 36.001 03/06/23 == | | AEV |
| | GENERAL CONVERSION | | AEV |
| 03-15-003H | **172"** F-550/450 4 x 4 (X-Series) Conv PKG 23-1 10/01/22 | | 1 AEV |
| 36-AA-0001 | WORK ORDER STATUS: | | 1 AEV |
| 00-90-0301 | For Confirmation | | 1 AEV |
| 36-CO-0001 | CHANGE ORDER POLICY | | 1 AEV |
| 36-CO-0010 | < After Confirmation, Prior to Engineering | | 1 AEV |
| | Change Fee is \$100 Per Item, Plus Option Cost | | |
| | | | |
| 36-CO-0030 | After Confirmation, After Production Start | | 1 AEV |
| | Change Fee is \$200 Per Item, Plus 200% Option Cost | | |
| | Additional labor charges above option costs may apply to accomodate the change | at | |
| | \$200 per hour. | | |
| | Special order or non-stocking parts that are purchased for any ordered option that | is | |
| | subsequently deleted will be charged for and shipped loose. | | |
| | >> | | |
| | Changes after production starts are the most disruptive. | | |
| | · | | |
| 36-CO-0035 | Change Order Recieved at Delivery ; | • | 1 AEV |
| | \$300 charge per item, plus three times the standard option cost AND Any addition | nal | |
| | labor to accomodate the change at \$200 per hour, | | |
| | Effective 01/28/2022 | | |
| | | | |
| 36-EO-0001 | ***END OF ORDER*** | i ' | 1 AEV |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |